DATASHEET

IO-SFP-CF-GS-LR

IO, 1G Optical Long Range SFP



Description

The IO-SFP-CF-GS-LR is a single mode SFP transceiver designed for Gigabit Ethernet and 1G Fiber Channel applications. It uses a 1310nm FP laser transmitter and a PIN photodiode receiver and supports transmission distances up to 10km on standard single mode fiber.

The module supports data rates up to 1.25Gbps and complies with the SFP Multi-Source Agreement and the SFF-8472 Digital Diagnostics Monitoring specification. The DDM interface provides real time reporting of temperature, voltage, transmit power, receive power and laser bias current.

The transceiver is available in Commercial 0°C to +70°C temperature variants, allowing deployment across various access and enterprise environments.

Key Specifications

- 1G SFP transceiver with duplex LC connector
- 1310nm FP transmitter and PIN photodiode receiver
- Supports 1.25Gbps Ethernet and 1.063Gbps Fiber Channel
- Up to 10km transmission distance over single mode fiber
- Power consumption around 1W
- Temp operating conditions: 0°C to +70°C

© 2026 HFCL Limited, All rights reserved.

IO-SFP-CF-GS-LR

IO, 1G Optical Long Range SFP



Technical Data

Parameter	Value	Parameter	Value
Form Factor	SFP	**Transmitter Data**	
Transmission Media	SM (LC)	Tx Power	-9 to 0dBm[1)]
Typical Reach	10km	Tx Wavelength	1260 -1360nm
Nominal Wavelength	1310nm	Extinction Ratio	≥ 9dB
Data Rate Support	10Mbps to 1.25Gbps	**Receiver Data**	
Protocol Support	GbE, 1G FC	Rx Sensitivity	-23dBm[1) 2)]
Power Consumption	<1.0W	Rx Overload, Max	-1dBm[2)]
Operating Temperature	0°C to 70°C	Rx Wavelength	1260 -1610nm
Storage Temperature	-40°C to 85°C	LOS Assert	-38dBm
DDM	Yes	LOS De-assert	-24dBm
		LOS Hysteresis	0.5dB

1. Average Power
2. @1250 Mbps, BER ≤1×10^{-12}, PRBS 2^7-1

© 2026 HFCL Limited, All rights reserved.

IO-SFP-CF-GS-LR

IO, 1G Optical Long Range SFP



Safety/Regulatory Compliance

- Class 1 laser safe
- RoHS Compliance

Absolute Maximum Rating

Parameter	Value
Supply Voltage	-0.5V to 3.75V
Storage Temperature	-40°C to 85°C
Relative Humidity	85%
Max Rx Optical Power	-1dBm

Ordering Information

Model No.	Description
IO-SFP-CF-GS-LR	IO, 1G Optical Long Range SFP Commercial Grade

Disclaimer: HFCL, IO by HFCL, and their respective logos are trademarks and/or registered trademarks of HFCL Limited. HFCL Limited assumes no responsibility for any inaccuracies in this document and reserves the right to revise or transfer this document without notice. All other trademarks, service marks, registered marks, or registered service marks mentioned herein are the property of their respective owners.

Last Updated 16 July 2026

Email: iosupport@hfcl.com
Website: hfcl.com | io.hfcl.com
Office: 8, Commercial Complex, Masjid Moth, Greater Kailash II, New Delhi 110048

© 2026 HFCL Limited, All rights reserved.