


The Most Compact and Versatile





www.peppermintrobotics.com









ROBOT SPECIFICATIONS	SD2X	
Battery Voltage, Nominal Capacity (V/Ah)	24/100	
Charger (Single Phase) (Automatic) (V/Amp)	24/22	
Charging Time (hrs)	5	
Max Power (W)	650	
Brush Motor (W)	200 x 1	
Vacuum Motor (W)	350	
Dry Weight (lbs)	375	
Sound Level (Db) ~70		
Dimensions (L x W x H) (inches)	31 x 28 x 37	
Turning Radius (Degrees)	Zero	

ROBOT SPECIFICATIONS	SD2X	CLEANING FUNCTIONS	SD2X
Battery Voltage, Nominal Capacity (V/Ah)	24/100	Type	Scrubber Dryer
Charger (Single Phase) (Automatic) (V/Amp)	24/22	Theoretical Productivity (sq.ft/hr)	16,660
Charging Time (hrs)	5	Cleaning Speed (m/s)	1
Max Power (W)	650	Squeegee Width (inches)	25
Brush Motor (W)	200 x 1	Scrubbing Width (inches)	17
Vacuum Motor (W)	350	Brush Rotation Speed (RPM)	600
Dry Weight (lbs)	375	Fresh Water Tank (Gal)	5
Sound Level (Db)	~70	Waste Water Tank (Gal)	5
Dimensions (L x W x H) (inches)	31 x 28 x 37	Electrical Protection Class	III
Turning Radius (Degrees)	Zero	Splash Water Protection Class	IPX3











Autonomous Operations

Up to 16,660 sq ft per hour.

Analytics & Reporting

operational and maintenance info of robots.

Real time dashboard for

Best In Class Battery Uptime

Highest operational time up to 4hrs per battery charge.

Round The Clock Support

Seamless maintenance and service support across all territories.







USA • EUROPE • MIDDLE EAST • INDIA



SCAN ME







Spares Supports

*All specifications are accurate at the time of testing at Peppermint Robotics. Actual performance may vary.