




Multilingual Interface

895 mm	823 mm
ROBOT SPECIFICATION	SD 20
Battery Voltage, Nominal	0.4./40/

ROBOT SPECIFICATION	SD 20CR
Battery Voltage, Nominal Capacity (V/Ah)	24/100
Charger (Single Phase) (Automatic) (V/Amp)	24/22
Charging Time (hrs)	5
Running Time (hrs)	5
Max Power (W)	665
Brush Motor (W)	200 x 1
Vacuum Motor (W)	350
Dry Weight (Kgs)	215
Sound Level (dB)	65
Dimensions (L x W x H) (mm)	823 x 895 x 1047
Turning Radius (Deg)	Zero

CLEANING FUNCTIONS	SD 20CR
Type	Cleanroom Scrubber Dryer
Max Theoretical Coverage (sq.mtr/hr)	928
Scrubbing Width (mm)	430
Suction Width (mm)	800
Brush Rotation Speed (RPM)	600
Fresh Water Tank (Ltr)	20
Waste Water Tank (Ltr)	20
HEPA Filter	H13



**Autonomous Operations** 

Up to 928 sq mtr


per hour.





## **Analytics & Reporting**

Real time dashboard for operational and maintenance info of robots.



## **Best In Class Battery Uptime**

Highest operational time up to 5hrs per battery charge.



## Round The Clock Support

Seamless maintenance and service support across all territories.









Certified





Service Support



Long Term **Spares Supports** 

- info@peppermintrobotics.com
- www.peppermintrobotics.com

- \*All specifications are accurate at the time of testing at Peppermint Robotics. Actual performance may vary.
- \*All information provided in the document is subject to change without prior notice.