

Quick Guide: Tear Gas Removal for Homeowners

SAFETY WARNING

Professional remediation is always the safest option. This guide is for emergency situations only.

Essential Safety Equipment

- Full-face respirator with chemical filters
- Protective coveralls or HAZMAT suit
- Chemical-resistant gloves
- Boot/shoe covers

Key Cleaning Equipment

- **Airbotx hydroxyl generator** (model 390X recommended)
- **Benefect Quantum Chemical Residue Remover**
- HEPA vacuum
- Microfiber cloths and disposable rags
- Heavy-duty plastic bags

5-Step Removal Process

1. VENTILATE & CONTAIN

- Open all windows and doors; turn OFF HVAC
- Put on all safety equipment before entering
- Deploy Airbotx hydroxyl generator in most contaminated area

2. REMOVE CONTAMINATED MATERIALS

- Remove and bag: carpet, curtains, upholstered furniture, paper products
- HEPA vacuum all remaining surfaces

3. DEEP CLEAN ALL SURFACES

- Apply Benefect Quantum undiluted to walls, floors, counters
- Let dwell 10 minutes, then wipe with fresh cloths
- Work top to bottom: ceilings → walls → floors
- Clean inside cabinets, drawers, and all hard contents

4. TREAT & TEST

- Run Airbotx continuously for 24-48 hours after cleaning
- Conduct sniff test with multiple people; re-clean if needed

5. HVAC & FINAL CLEANUP

- Have HVAC system professionally cleaned before turning back on
- Continue running Airbotx for several days

Expected Timeline

- **Day 0-1:** Ventilation, removal, Airbotx deployment
- **Day 1-2:** Deep cleaning with Benefect Quantum
- **Day 3-5:** Continued treatment, testing, re-cleaning
- **Day 5-7:** HVAC cleaning, final assessment

Need Professional Help?

Umpire Mitigation • 703-665-1129 • Available 24/7