



Ph: 866.710.2837 | [www.AterCompany.com](http://www.AterCompany.com)

## SUBMERSIBLE SOLIDS HANDLING PUMP

**Series: AP2V.SS.L**

0.5 & 0.75 HP

1750 RPM

Discharge: 2 or 3"

Spherical Solids Handling: 2"

### DISCHARGE

2" or 3" NPT female, vertical, bolt on flange.

### LIQUID TEMPERATURE

104 °F (40 °C) continuous

### VOLUTE

Cast iron ASTM A-48 class 30

### MOTOR HOUSING

Cast iron ASTM A-48 class 30

### SEAL PLATE

Cast iron ASTM A-48 class 30

### IMPELLER

**Design:** 2 vane, open, with vanes on back side.

**Material:** cast iron ASTM A-48 class 30

### SHAFT

416 series stainless steel

### HARDWARE

300 series stainless steel

### SQUARE RINGS

Buna-N

### PAINT

Air dry enamel, water based.



### SEAL

**Design:** inboard single mechanical, oil filled chamber.

**Material:** silicon carbide, Buna-N elastomer and stainless steel hardware.

### CORD ENTRY

30 ft of neoprene cord SJO 14/3, sealed against moisture.

### BEARINGS

**Upper:** ball, single row, oil lubricated, for radial load.

**Lower:** ball, single row, oil lubricated, for radial and thrust load.



### MOTOR

**Single phase:** NEMA L, permanent split capacitor, 115 & 230 volts, 60 Hz, 1750 RPM, oil filled, overload protection in motor.

**Three phase:** NEMA B, 200/230 & 460 volts, 60 Hz, 1750 RPM, oil filled. Requires overload protection to be included in control panel.

### OPTIONAL EQUIPMENT

**Includes 3" discharge flange.**



| MODEL          | HP   | VOLTS   | PHASE | RPM (NOMINAL) | MAX AMPS | LOCKED ROTOR AMPS | NEMA CODE | CORD SIZE | CORD TYPE | CORD O.D. | WEIGHT (LBS) |
|----------------|------|---------|-------|---------------|----------|-------------------|-----------|-----------|-----------|-----------|--------------|
| AP2V.5SS11L17  | 0.5  | 115     | 1     | 1750          | 11.6     | 18.4              | D         | 14/3      | SJO       | 0.5       | 91           |
| AP2V.5SS21L17  | 0.5  | 200/230 | 1     | 1750          | 5.9      | 14.9              | B         | 14/3      | SJO       | 0.5       | 93           |
| AP2V.5SS23L17  | 0.5  | 200/230 | 3     | 1750          | 4.6/4.2  | 9.7/11.1          | K         | 14/3      | SJO       | 0.5       | 95           |
| AP2V.5SS43L17  | 0.5  | 460     | 3     | 1750          | 2.2      | 5.3               | K         | 14/3      | SJO       | 0.5       | 95           |
| AP2V.75SS21L17 | 0.75 | 230     | 1     | 1750          | 10.5     | 17.5              | D         | 14/3      | SJO       | 0.5       | 95           |
| AP2V.75SS23L17 | 0.75 | 200/230 | 3     | 1750          | 5.5      | 16                | D         | 4-Dec     | SJO       | 0.625     | 96           |
| AP2V.75SS43L17 | 0.75 | 460     | 3     | 1750          | 2.2      | 8                 | D         | 4-Dec     | SJO       | 0.625     | 96           |

**IMPORTANT!** 1.Never use this pump to handle explosive liquids. 2. This pump is not approved to be used in swimming pools, recreational installations or any application where human contact may be common. 3. Pump may be operated "dry" for extended periods without damage to motor and/or seals.