Scaling IoT Solution Without Scaling Costs

Technical Report

Introduction

Overview of IoT Multi-Asset Platforms

A multi-asset IoT platform enables seamless connectivity, data collection, and management for multiple asset types (e.g., industrial sensors, smart devices, vehicles). Scaling this platform for millions of devices requires robust data pipelines, efficient storage, and secure connectivity.

Purpose & Scope

This report evaluates the cloud-based components of our Industrial IoT (IIoT) solution to determine readiness and feasibility for scaling. It focuses on software architectures, cloud services, and infrastructure optimizations needed to support exponential growth in data volume, device count, and user demand.

Target Audience

Cloud architects, DevOps teams, software engineers, and technical decision-makers responsible for the cloud infrastructure.

Methodology

- **Interviews & Documentation Reviews:** Gathered feedback from cloud operations engineers, application developers, and security specialists.
- **Performance Metrics & Load Testing:** Analyzed logs and test results from staging environments to identify bottlenecks.
- **Cost Analysis & Forecasting:** Projected near-term and long-term consumption of cloud resources to estimate scaling costs.

Importance of Scalability & Performance

Handling millions of devices requires a system capable of:

- Managing **millions of concurrent connections** efficiently.
- Processing **real-time data** at high throughput.
- Storing **large volumes of telemetry data** with low-latency access.
- Scaling **horizontally** across cloud-based and edge environments.

Architecture Overview

Overview of IoT Multi-Asset Platforms



Key Components and Their Roles

- **Device Gateway (MQTT, HTTP, WebSockets)** – Connects IoT devices to the cloud.
- **Data Ingestion - Azure IoT HUB, MQTT, AWS IoT Core, Google Cloud IoT Core,** For Message Broking.
- **Streaming & Queueing:** [e.g., Kafka, Amazon Kinesis, Azure Event Hubs, or Google Pub/Sub] for real-time data pipelines. Manages high-throughput message ingestion.
- **Data Processing (Apache Spark)** – Processes telemetry data in real-time. Batch Processing for Historical Data Aggregation.
- **Storage (PostgreSQL, MongoDB, Redis)** – Stores structured, unstructured, and cached data.

- **Microservices (Spring Boot)** – Manages business logic and APIs.
  - IAM, role-based access control, encryption at rest (KMS, SSE), encryption in transit (TLS).
  - Logging, auditing, and alerting frameworks
- **Security & Monitoring (IAM, TLS, Prometheus, Grafana)** – Secures and monitors the platform.
- **Resource Utilization:**
  - **Compute:** Current usage for CPU, memory, GPU (if applicable).
  - **Storage:** Data growth rate, partitioning strategy, archival processes.
  - **Network:** Ingestion throughput, average vs. peak concurrency, bandwidth usage across regions.

Performance Baseline and Growth Projections

Current Workloads:

- **Data ingestion rate:** X messages/second.
- **Concurrent users:** X daily active users or operator dashboards.
- **Storage consumption:** X GB/day of raw sensor data.

Projected Growth:

- Estimated to double or triple ingestion volume in the next 12 months if the solution expands to multiple manufacturing sites or product lines.
- Increased usage of analytics and machine learning—driving up computational loads (training and inference).

Performance Metrics & SLAs:

- Current latency for device-to-cloud messaging: X ms (target: ≤100 ms).
- API response time: X ms p95 (target: ≤300 ms).
- Availability: 99.5% monthly (target: 99.9%+).

Scalability Requirements and Constraints

Technical Requirements:

- **Auto-Scaling:** Ability to dynamically adjust compute, storage, and network resources based on real-time loads and throughput demands.
- **Global Availability:** Multi-region or multi-availability-zone architecture to reduce latency and improve fault tolerance.
- **Data Lifecycle Management:** Automated tiering or archiving of older sensor data to manage storage costs.

Business Constraints:

- **Budgetary Limits:** Cloud spend must remain within X% of operational budget with clear ROI.
- **Regulatory Compliance:** Some data may require in-region storage, impacting architecture choices (GDPR, HIPAA, etc.).

Risk Factors:

- **Vendor Lock-In:** Limited portability if proprietary cloud services are heavily used.
- **Security Complexity:** Scaling to thousands of devices in multiple regions increases the risk of misconfigurations and potential breaches.

Proposed Cloud Upgrades and Services

Enhanced Data Streaming Architecture:

- Switch from single to multi-stream approach or partition by device groups to balance loads.

Autoscaling Improvements:

- Implement target-based autoscaling for container clusters (e.g., Kubernetes HPA/VPA) and serverless concurrency settings.
- Define custom metrics (not just CPU/memory) for scaling triggers, such as queue backlog or throughput rates.

Database Optimization:

- Migrate to a globally distributed NoSQL database (e.g., MongoDB, Cosmos DB, Spanner) or leverage read replicas in multiple regions.
- Use partitioning / bucketing strategies to handle large time-series data sets efficiently.
- Implement data lifecycle policies for cold storage or archival (e.g., Amazon S3 Glacier, Azure Archive Storage).

Observability & Incident Response:

- Deploy a centralized monitoring/observability platform (e.g., AWS Observability Accelerator, Azure Monitor with Log Analytics) for metrics, logs, and traces.
- Automate alerting via integration with incident response tools (e.g., PagerDuty, Opsgenie).

Security Enhancements:

- Employ device-level security certificates and rotate credentials automatically.
- Expand the use of encryption keys and expand or refine key management policies.
- Harden network perimeters using private links, VPC endpoints, or service endpoints to reduce public exposure.

Scale Ready Implementation Details

Device Communication & Messaging

- **Protocol Selection:**
  - Use **MQTT** for lightweight, low-latency messaging. Consider WebSockets for web-based real-time communication and AMQP for transactional messaging.
  - Use **IoT HUB** as a central hub for IoT device communication, enabling secure and reliable messaging between devices and applications. Provides limited MQTT support, focusing on device-to-cloud and cloud-to-device communication.
  - Use **Azure Event Grid**, that offers more comprehensive MQTT support, including bi-directional communication and routing to other Azure services.
- **Load Balancing:** Deploy multiple MQTT brokers (e.g., EMQX, Mosquitto, or Azure IoT Hub) with a load balancer to handle connections efficiently.
- **Message Throughput Optimization:**
  - Optimize [illegible]

- **Event-Driven Architecture:** Integrate Kafka/Event Hub for reliable, decoupled event processing. Use Kafka Streams or Spark Streaming for real-time data analytics.
- **Edge Computing:** Process critical data at the edge to reduce cloud load and improve response time.

Data Processing Pipeline

- Ingestion Layer:
  - Use **Azure Event Hub / Kafka** for handling high-throughput ingestion.
  - Use **Kafka** for stream processing with partitioning for scalability.
- Stream Processing:
  - Use **Apache Spark Structured Streaming** or **Kafka Streams** to process real-time data efficiently, Harness
  - Implement
- Data Transformation & Enrichment:
  - Use **Apache Spark** for real-time aggregation, batch-aggregation, filtering, and anomaly detection.
  - Enrich data with metadata from Redis or a NoSQL database (MongoDB).
- Storage Integration:
  - Send raw/processed data to **PostgreSQL (time-series data)** and **MongoDB (JSON documents, device configs)**.

Database & Storage Optimization

- Time-Series Data Optimization:
  - Use **TimescaleDB (PostgreSQL extension)** or **InfluxDB** for efficient storage.
- NoSQL Optimization:
  - Use **MongoDB sharding** for horizontal scalability. Revisit

- Store device configurations and metadata in **key-value stores (Redis, DynamoDB)**.

- **Cold vs. Hot Storage:**

- **Data Caching:**

Microservices Deployment & Scaling

- **Containerization:**
  - Use Docker and Kubernetes (K8s) for microservices deployment.
  - Optimize
- **Service Communication:**
  - Use **gRPC** for low-latency microservice communication.
  - Implement **message brokers (Kafka, RabbitMQ)** for event-driven workflows.
- **API Gateway & Load Balancing:**
  - Deploy **NGINX, Traefik, or Azure API Gateway** to manage API traffic.
  - Use **Istio or Linkerd** for service mesh and observability.
- **CI/CD Pipelines:**
  - Automate deployments using **GitHub Actions, ArgoCD, or Jenkins**.
  - Use **Helm charts** for Kubernetes deployment automation.

OS Hardening and Configuration optimization

- OS Configuration optimization plays an important role to support scale in an IoT Platform.
- Disable Unnecessary Services & Ports
- Enforce Strong Authentication & Least Privilege
- Optimize Network Stack for High Concurrent Connections

- Increase allowed

```bash
sysctl 535
sysctl 535
sysctl 0000
```

- Enable

```bash
sysctl 3
```

- Increase
  Increase

```bash
sysctl 65535"
```

- Keep Connections

```bash
sysctl 20 #Default:7200 (2 hrs), Reduce to 120
sysctl 0 #Default: 75 sec, Reduce to 30 sec
sysctl 5 #Default: 9, Reduce to 5
```

  Keeps long-lived IoT connections

- Optimize SYN
  - Increase
  - Reduce
- Optimize
  - Enable
  - Enable Useful for **10Gbps+ network interfaces.**

- Increase

- Connection Throttling & Rate Limiting

- Optimize Packet & Buffer Sizes -

- Use a High-Performance Filesystem

- Optimize Kernel for Low Latency & High Throughput

- Enable

- Load

nginx Copy Edit

```
keepalive 0;
keepalive 000;
worker_ 35;
```

Allows multiple requests per connection to **reduce overhead.**

Security Best Practices

- Device Authentication & Authorization:

- Data Encryption:

- Zero Trust & Role-Based Access Control (RBAC):

- Threat Detection & Monitoring:

Cost Optimization Strategies

- Cloud Resource Scaling:

- Storage Cost Reduction:

- Efficient Event Processing:

- CI/CD Optimization:

Optimizing Apache Spark, Kafka, Kafka Connect, MongoDB, PostgreSQL, Redis, MQTT

- Apache Spark Optimization
  - Enable
  - Choose right number of cores & memory per executor.
  - Optimize shuffle partitions for parallelism.
  - Avoid
  - Avoid
- Kafka Optimization
  - Increase topic partitions **(Do not over partition the topics)**.
  - Apply
  - Use General
  - Enable
  - Optimize broker/consumer/producer level configs as per the requirement.

Throughput & I/O

```properties
num.8
num.6
queued.00
socket.8576          # 1MB
socket.8576          # 1MB
socket.57600         # 100MB
```

Message Size & Log

```properties
message.8576         # 1MB max message size
replica.7152         # 2MB per fetch request
log.1824             # 1GB segments
log.72
log.retention.bytes=-1
```

Replication & Recovery

properties

```
num.                    4
replica.                1
replica.                00
unclean.                false
```

Memory & Page Cache

properties

```
log.                    00
log.                    0
log.                    000
```

Producer Configs

properties

```
acks=1                                  # or "all" for guaranteed delivery (slower)
compression.            4               # faster and smaller than gzip
batch.                  36              # 64KB
linger.                                 # small  delay to allow batching
buffer.                 4432            # 32MB
max.                    8576            # 1MB
retries=
retry.                  0
```

Consumer Configs

properties

```
fetch.                  68              # o32KB
fetch.                  576             # 1MB
max.                    576             # 1MB per partition
fetch.                  00              # Wait longer to fill batch
enable.                 false           # Better to control manually
max.                    00              # Tune based on processing time
max.                    00
session.                000
heartbeat.              0
```

- **Rule of Thumb Calculation**
  - Eg. 20,000 msg/sec × 5KB Msg Size = **100MB/sec total**
  - Assuming 3 brokers:

- **Kafka Connect Optimization**
  - Use **distributed mode** for high scalability.

- **MongoDB Optimization**
  - Use Sharded MongoDB to handle large volume of timeseries data. § Use nesting of timeseries data per asset_id (bucketing) per hour, day.
  - **Use compound indexes** for complex queries.
  - Implement **sharding** for scalability.
  - Apply TTL on each data table to prevent disk over out of space issues.
  - Use Provisioned IOPS SSDs (io1/io2) to maximize the write throughput and support 100-thousands writes per second.
  - Use Memory Optimized VMs maximize the read/write throughput.

- **PostgreSQL Optimization**
  - Optimize
  - Enable

- **Redis Optimization**
  - Use
  - Enable

- MQTT Optimization
    - Apply OS level optimizations (discussed above).
    - Create Shared topics to enable distributed/parallel data processing for other apps/consumers (Kafka Connect / Apache Spark etc)
    - Deploy **scalable brokers (EMQX, HiveMQ)**.
    - Apply Role based access on client id for each publisher and subscriber.
    - Optimize **keep-alive intervals.**

Testing & Validation Strategy

Load & Stress Tests:

- Conduct synthetic load tests simulating X, 2X, and 5X the current ingestion rate to validate performance at scale.
- Use chaos engineering or fault-injection testing to assess resilience under node or service failures.

Performance Benchmarks & Profiling:

- Profile the entire data flow (from edge device messages to analytics dashboards) to pinpoint high-latency segments.
- Measure resource utilization during peak loads and identify oversizing or undersizing in certain components.

Security & Penetration Testing:

- Validate encryption, authentication, and role-based access policies under scaled environments.
- Perform regular penetration tests to ensure no new vulnerabilities emerge as the architecture expands.

Cost Analysis and Optimization

Current Cloud Spend:

- Monthly average: $X.
- Breakdown by service: ingestion pipeline (30%), compute (40%), storage (20%), networking (10%).

Forecasting and Budget Impact:

- Projected growth may double monthly costs within 12 to 18 months if usage patterns persist.
- Potential cost spikes in data egress or serverless concurrency fees.

Optimization Strategies:

- **Reserved/Committed Instances:** Lock in reserved capacity or commit to multi-year plans (e.g., AWS Savings Plans, Azure Reserved Instances).
- **Cost-Aware Application Design:** Filter and aggregate data at the edge to reduce unnecessary cloud ingestion.
- **Auto-Shutdown Policies:** Automate shutting down non-production resources to minimize idle costs.

Recommendations and Roadmap

Immediate (0–3 Months):

- Implement advanced autoscaling policies.
- Initiate data lifecycle management for older or less critical sensor data.
- Consolidate observability tools for unified alerting and monitoring.

Mid-Term (3–6 Months):

- Migrate to or upgrade a globally distributed database for lower-latency writes in additional regions.
- Conduct large-scale load and chaos tests to refine high-availability strategies.
- Begin pilot usage of container orchestration or serverless compute expansions in new regions.

Long-Term (6–12 Months):

- Optimize cross-region replication and failover for zero-downtime resilience.
- Fully implement continuous integration/continuous deployment (CI/CD) pipelines with infrastructure as code for consistent multi-region rollouts.
- Evaluate new cloud-native services (machine learning, real-time analytics) for further automation and predictive insights.

Conclusion & Future Enhancements

Scaling the Industrial IoT cloud software stack requires a comprehensive approach that addresses **architecture design, performance engineering, cost optimization, and security.** By methodically implementing the recommendations in this report—autoscaling, global deployments, optimized databases, and improved observability—the organization can handle exponential data growth and achieve high availability, low latency, and robust security at scale.

Next Steps:

- Review and finalize the proposed roadmap with engineering leadership.
- Allocate the required budget and assign resources (DevOps, security teams, etc.) to execute recommended improvements.
- Establish KPI targets for latency, throughput, and cost, and track them rigorously to measure success.
- Implement **AI-driven predictive analytics**.
- Expand **multi-cloud architectures.**
- Explore **serverless computing** for event processing.