



Crown Tropical Latex

Basic Uses: interior/ exterior surfaces

LATEX PAINT



TECHNICAL DATA

VISCOSITY: 108-113 KU's
DENSITY: 10.40 ±0.05 lbs/gal
FLASH POINT: Non-flammable
SOLIDS (WEIGHT): 50%
DRY FILM THICKNESS: At a rate of
125 ft²/gal: 4 mil wet, 1.7 mils dry
V.O.C.: <50g/L

SIZES

1 gallon
5 gallons

FINISH

Flat (0-5%) @
Geometry 60°

COLOR

White
Bone white

DESCRIPTION

A quick drying interior / exterior paint climate-tailored for the tropics. It combines ease of application with good durability and color retention.

DIRECTIONS

SURFACE PREPARATION:

Apply only on surfaces free of dust, grease, wax or mildew. Two coats are recommended.

PREVIOUSLY PAINTED SURFACES:

Either surface must be clean to obtain proper adhesion.

METHOD OF APPLICATION:

Stir well before applying. Apply with brush, roller or spray.

THINNING:

Not normally recommended, but if necessary thin with only ½ pint of clean water to the gallon.

DRYING TIME

Tack free between 30 - 45 minutes.
Allow drying 4 hours between coats.

COVERAGE:

250-400 sq. ft. per gallon, depending on surface texture and porosity.

CLEAN UP:

Wipe off drips and spatters using a wet cloth with soap and water. Clean

equipment with soap and water.

PRECAUTIONS

Do not take internally. Close container after each use.

KEEP OUT OF THE REACH OF CHILDREN!