

NEXIS-M

IP67 IK08  



CRI
80



L80B10
50.000h



CODE NE02


TYPOLGY Recessed
INSTALLATION POSITION In Ground
INSTALLATION LOCATION Outdoor

NEXIS-M

POWER 2.2W

WEIGHT 0.18KG

DIMENSION 42 mm



ELECTRICAL FEATURES

POWER CONSUMPTION	2.2 W for 24 Vdc or 1.6 W for C.C
POWER SUPPLY	24VDC Or C.C
POWER SUPPLY UNIT	Remote
DIMMING	On/Off
CONNECTION	Series for C.C / Parallel for 24Vdc

LIGHTING FEATURES


LED COLOR	2200K, 2700K, 3000K, 4000K
CRI	>80
OPTICS	10°, 36°, 60°, 67x16 ,Diffused
TOTAL DELIVERD LUMENS	152 lm (10°), 130 lm (36°), 121 lm (60°)
TOTAL NOMINAL LUMENS	180 lm (2700K), 190 lm (3000K), 200 lm (4000K)
AVERAGE LED LIFE	50.000h L80 B10

GENERAL FEATURES


OPERATING TEMPERATURE	50°C
INGRESS PROTECTION	IP67
IMPACT RESISTANCE	IK08
GLOW WIRE TEST	960°C
SCREEN TEMPERATURE	40° @ Ta = 25°
APPLIANCE CLASS	I
WALKOVER	Yes
DRIVE OVER	Yes
TEMPERED GLASS	Yes
POWER CABLES	Provided with 50 cm cable
STANDARD SAFETY	/
PHOTOBIOLOGICAL SAFETY	GR1
MATERIAL	Aluminium Alloy 6082 Body / Aluminium or AISI 316L Stainless Steel

ACCESSORIES

NEXIS-M



CODE *VIHB*
TYPOLGY *Housing box*
WEIGHT *15g*
MATERIAL *Polyethylene*



CODE *HC*
TYPOLGY *Filter*
WEIGHT *0.14 G*
MATERIAL *Aluminium*