



**PRECISION
LUBRICATION**

CALCIUM SULPHONATE EP 2 GREASE

Description

Calcium Sulphonate EP 2 Grease is a blend of calcium sulphonate NLGI 2 grease, which is an excellent lubricant for high temperature and wet industrial and automotive applications. This grease provides outstanding mechanical and thermal stability, has very high load carrying characteristics and provides good resistance to corrosion in the presence of water.

Applications

Calcium Sulphonate EP 2 Grease is recommended for large plain and anti-friction bearings as well as mechanisms, which require high temperature grease such as slides and cams. It has good adhesive qualities, good pumpability and reduces re-lubrication intervals.

Features/Benefits

- Operating temperatures from -15 °C to +160 °C
- Provides high resistance to water wash-out and spray-off
- Outstanding corrosion and rust protection
- Excellent load carrying ability
- Acts as a sealant against dust

TYPICAL PHYSICAL CHARACTERISTICS

TEST	TYPICAL RESULTS
NLGI Number	2
Thickener Type	Calcium Sulphonate
Worked Penetration @ 25°C	265 - 295
Drop Point °C	>280
Oil Viscosity cSt @ 40°C	200
Timken OK Load, kg	27
Appearance	Beige Brown

DISCLAIMER: The information given in this document is offered in good faith, but no warranty is implied or expressed. The onus is on the end user to ensure the suitability of this product to meet the end user requirements. It is also the end user's responsibility to follow health & safety procedures when using this product.

