



PRECISION
LUBRICATION

WHITE OIL 46

Description

White Oil 46 is resistant to the formation of deposits, which could create fire and explosion hazards. The product is manufactured from paraffinic stock of high Viscosity Index; these properties are further enhanced by the incorporation of additives, which give a unique control over oxidation, rust, corrosion and wear.

Applications

White Oil 46 is recommended for crankcase and cylinder lubrication of reciprocating air compressors and for rotary vane and screw compressors requiring mineral oils

Features/Benefits

- Superior oxidation stability – Extended drain intervals
- Reduced compressor deposits – Narrow distillation range base oils
- Reduced fire and explosion risks
- Reduced wear – Inhibits friction, corrosion and rust
- Reduced crankcase oil consumption – High viscosity index

TECHNICAL DATA

TEST	TYPICAL RESULTS
Viscosity, cSt @ 40°C cSt @ 100°C	46 7,0
Viscosity Index, min.	95
Viscosity Index, min.	199
Pour Point, °C, max.	-18
ISO VG	46c

DISCLAIMER: The information given in this document is offered in good faith, but no warranty is implied or expressed. The onus is on the end user to ensure the suitability of this product to meet the end user requirements. It is also the end user's responsibility to follow health & safety procedures when using this product.

