PRECISION LUBRICATION

# MATERIAL SAFETY DATA SHEET

| | |
|---|---|
| Product Name | SIRIUS EP/XD HEAVY DUTY GREASE NLGI 2 |
| Product Code | 9003 20850 |
| Symbols | Not Classified |
| Labeling for Transport | Not Classified |

## SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

| | |
|---|---|
| **Product Name** | 9003 20850 |
| **Supplier** | NOVA INDUSTRIAL CC |
| **Updated** | Apr. 2023 |
| **Review** | Apri 2025 |
| **CAS-Number** | N/A |
| **UN Number** | N/A |
| **Health Emergency Telephone** | (011) - Red Cross Poison |
| **Transport Emergency Telephone** | (011) 331 2161 (Macsteel) |

A petroleum product. DMSO extract < 3 % weight ( IP 346 )

## SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients considered hazardous to Health:

| | |
|---|---|
| **Mixtures Distillates (petroleum) solvent-dewaxed heavy paraffinic** | 60-100% |
| **CAS-number: 64742-65-0** | EC number: 265-169-7 REACH registration number: 01-2119471299-27-XXXX |

## SECTION 3. HAZARDOUS IDENTIFICATION

| | |
|---|---|
| **US OSHA Hazard communication Standard** | Product assessed in accordance with OSHA 29 CFR 1910.1200 and determined not to be hazardous. |
| **Note** | Keep good personal hygiene and avoid prolonged exposure. |
| **Emergency Response Data** | Lubricating Grease |

Note: Under normal conditions of intended use, this product does not pose a risk to health. Excessive exposure may result in eye, skin and respiratory irritation

See Section 11 for further health effects/toxicological data.

## SECTION 4. FIRST AID MEASURES

| | |
|---|---|
| **Inhalation** | Not expected to be a problem. However, if respiratory irritation occurs due to excessive vapour or dust exposure, seek immediate medical attention. If breathing has stopped, apply artificial respiration. Keep victim warm and rested. Do not induce vomiting. |
| **Skin** | Remove contaminated clothing. Dry wipe exposed skin and cleanse with hand cleaner, soap and water. Launder contaminated clothing before reuse. Seek medical attention if irritation occurs. |
| **Eyes** | Flush thoroughly with water. If irritation occurs call a doctor. |
| **Ingestion** | Not expected to be a problem. However, if discomfort occurs seek medical attention. Do not induce vomiting. |

## SECTION 5. FIRE FIGHTING MEASURES

| | |
|---|---|
| **Extinguishing media** | Carbon dioxide, foam, dry chemical and water fog. |
| **Special Fire-fighting procedures** | Water or foam may cause frothing. Use water to keep fire exposed containers cool. When spray may be used to flush spills away from exposure. Prevent runoff from fire control or dilution from entering streams, municipal water supplies or underground areas. |
| **Special protective equipment** | For fires in enclosed areas, fire fighters must use Self-Contained Breathing Apparatus. |
| **Unusual fire and explosion hazards** | None |
| **Products of decomposition** | Fumes, smoke, carbon monoxide, sulphur oxides, aldehydes and other decomposition products. In the case of incomplete combustion. |
| **Flashpoint C** | > 199 °C (ASTM D-92) |

NFPA Hazard ID

| | |
|---|---|
| **Health** | 0 |
| **Flammability** | 1 |
| **Reactivity** | 0 |
| **Hazardous decomposition products** | Carbon Dioxide Carbon Monoxide |

## SECTION 6. ACCIDENTAL RELEASE MEASURES

| | |
|---|---|
| **Notification procedures** | Report spills/releases as required to appropriate authorities |
| **Procedures if the materials is released or spilled Environmental precautions** | Shut off source taking normal safety precautions. Take measures to minimize spillage. Contain spillage using sand, earth or other suitable absorbent. Use equipment or current spilled liquid with sand or other suitable absorbent and remove mechanically into containers. Prevent spills from entering storm sewers or drains and contact with soil. |
| **Personal precautions** | See Section 13 |

## SECTION 7. HANDLING AND STORAGE

Occupational exposure limits Distillates (petroleum) solvent-dewaxed heavy paraffinic
Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.
Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield.

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. Wear protective gloves made of the following material: Nitrile rubber, Polyvinyl chloride (PVC).

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Wear protective gloves made of the following material: Nitrile rubber, Polyvinyl chloride (PVC).

## SECTION 8. EXPOSURE CONTROL/PERSONAL PROTECTION

| | |
|---|---|
| **Ventilation** | No special requirement under ordinary conditions of use and with adequate ventilation. |
| **Respiratory Protection** | No special requirements under ordinary conditions of use and with adequate ventilation. |
| **Eye Protection** | Normal industrial eye protection when handling liquids should be worn. |
| **Skin Protection** | Use chemical-resistant apron and/or other clothing to avoid contact. |

Occupational exposure limits:

| | LTEL | STEL | NOTE |
|---|---|---|---|
| Substance name (CAS-No) | | | |
| Asphalts (petroleum) | | | |

N/A = Not Applicable, N/E = Not Established, D = Decomposes
For further technical information, contact your marketing representative.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|---|
| **Appearance** | Liquid |
| **Colour** | Amber |
| **Odour** | Mild |
| **pH** | N/A |
| **Boiling Point (Celsius)** | N/A |
| **Flash Point** | > 220 °C (ASTM D-92) |
| **Flammability** | Flammable |
| **Auto Flammability** | N/E |
| **Explosive Properties** | N/A |
| **Oxidizing Properties** | N/A |
| **Vapor pressure mmHg 20OC** | < 0.1 kPa |
| **Density at 20°C** | 0.897 g/cm3 @ 15 °C (ASTM D-4052) |
| **Solubility in water** | Negligible |
| **Pour point** | -27°C |
| **Viscosity** | 115 cst @100°C |

N/A = Not Applicable, N/E = Not Established, D = Decomposes
For further technical information, contact your marketing representative.

## SECTION 10. STABILITY AND REACTIVITY

| | |
|---|---|
| **Reactivity** | No specific test data related to reactivity available for this product or ingredients. |
| **Chemical stability** | The product is stable |
| **Possibility of hazardous reactions** | Under normal conditions of storage and use, hazardous reactions will not occur. |
| **Conditions to avoid** | Extreme heat and high energy sources of ignition, such as sparks and static electricity. |
| **Incompatible materials** | Strong oxidizers |
| **Hazardous decomposition products** | Fumes, smoke, carbon monoxide, sulphur oxides, aldehydes and other decomposition products, in the case of incomplete combustion |

## SECTION 11. TOXICOLOGICAL INFORMATION

| | |
|---|---|
| **Oral toxicity** | Practically non-toxic (LD50: Greater than 2000 mg/kg). Based on testing of similar products and/or the components. |
| **Dermal toxicity** | Practically non-toxic (LD50: greater than 2000 mg/kg). Based on testing of similar products and/or the components. |
| **Inhalation toxicity** | Practically non-toxic (LC50: greater than 5mg/l). Based on testing of similar products and/or the components. |
| **Eye irritation** | Slightly irritating. Drying action greater than 8 out 10 in test. Based on testing of similar products and/or the components. |
| **Skin irritation** | Practically non-irritating. Primary irritation index: greater than 0.5 but less than 5. Based on testing of similar products and/or the components. |
| **Other toxicity data** | Although at acute inhalation study was not performed with this product in a variety of mineral and synthetic oils, such as those in this product, significant toxicological effects were not found. Long term exposure to nonaspecific inflammatory response in the lung to the aerosolized mineral oil. Mineral oil pneumonia is not expected to occur under normal exposures to saleable amounts as in the product. Prolonged or repeated exposure to mineral oil may result in oil deposit dependent chronic granulomatous inflammation. |
| **Sensitisation:** | Not expected to be sensitising based on tests of this product, components, or similar products. |
| **Repeated dose toxicity** | No significant adverse effects were found in studies using repeated dermal applications of similar lubricants to the skin of laboratory animals for 90 weeks or doses significantly higher than those expected during normal handling. Similar lubricants were not found to cause cancer in long term skin painting, inhalation, ocular, intraperitoneal, and/or subcutaneous studies with laboratory animals. Repeated and/or prolonged exposure may cause irritation to the skin, eyes or respiratory system. |
| **Teratogenicity** | No teratogenic effects would be expected from dermal exposure, based on studies with laboratory animals exposed to similar lubricants. Refer to the Inhalation and/or exposure of skin sections. |
| **Carcinogenicity** | Chronic mouse skin painting studies of severely solvent refined mineral base oils showed an evidence of significant tumorigenic effects. Solvent base oils have been shown to be non-carcinogenic in similar studies. Highly refined base oils are not known to be carcinogenic with chronic dermal exposure. |

## SECTION 12. ECOLOGICAL INFORMATION

| | |
|---|---|
| **Biodegradability** | This product is expected to be inherently biodegradable |
| **Physico-chemical Removability** | Absorption to sediment and soil will not be the predominant behaviour |
| **Bioaccumulation** | Minimal owing to low water solubility. |

**Ecotoxicity effects**

| | |
|---|---|
| **Toxicity to aquatic organisms** | This substance is practically non-toxic to aquatic organisms (LL50 >1000 mg/l) |

**Further information on ecology**

| | |
|---|---|
| **Remarks** | In the absence of specific environmental data for this product, this assessment is based on information for representative substances. |

## SECTION 13. DISPOSAL INFORMATION

**Waste disposal:** Product is suitable for burning in an enclosed, controlled burner for fuel value or disposal by licensed contractor in accordance with local regulations.
Recycle wherever possible. Consult your Environmental Conservation and Recycling Agency. In addition, the product should be considered for energy recovery or recycling. Recycling is to be disposed of at any government approved waste disposal facility. Use of these methods is subject to user compliance with applicable laws and regulations and considerations of product characteristics at time of disposal.

Empty containers retain residue (may contain product residue) and/or vapour) and can be dangerous. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Do not attempt to refill or clean containers since residue is difficult to remove. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner or other responsible party for disposal of in an environmentally safe manner and in accordance with governmental regulations.

**Other regulations:** The unused product, in our opinion, is not specifically listed by the EPA as a hazardous waste (40 CFR, Part 261D), nor is it formulated to contain materials which are listed hazardous wastes. It does not exhibit the hazardous characteristics of ignitability, corrosivity, or reactivity and is not formulated with contaminants as determined by the Toxicity Characteristic Leaching Procedure (TCLP). However, used product may be regulated.

Dispose of waste at an appropriate waste disposal facility in accordance with current applicable laws and regulations, and product characteristics at time of disposal.

**Flash Point:** > 189 °C (ASTM D-92)

## SECTION 14. TRANSPORT INFORMATION

This product is not regulated by the following: U.S. DOT (CFR), ADR, IATA and IMDG.

## SECTION 15. REGULATORY INFORMATION

US OSHA Hazard
Communication Standard: When used for its intended purposes, this product is not classified as hazardous in accordance with OSHA 29 CFR 1910.1200.

Governmental Inventory
Status: All components comply with TSCA, EINECS/ELINCS, AICS, METI, DSL, KECI, ENCS, PICCS and IECSC.

EU Labelling: Product is not dangerous as defined by the European Union Dangerous Substances'
Preparations Directives. EU labelling not required.

**SARA**

U.S. Superfund This product contains no "EXTREMELY HAZARDOUS SUBSTANCES" SUBSTANCES
Reauthorization Act SARA
Title
III (40 CFR 372) Reportable
Hazard Categories: None

**The following product ingredients are cited on the lists below**

| Chemical Name | CAS Number | List Citations |
|---|---|---|
| Paraffinic Extract | 64742-54-7 | 2,17 |

**Regulatory list searched**

| | |
|---|---|
| **1 - ACGIH ALL** | **14 - TSCA 6** |
| **2 - ACGIH A1** | **15 - TSCA 12b** |
| **3 - ACGIH A2** | **16 - CA P65** |
| **4 - NTP** | **17 - CA RTK** |
| **5 - NTP A** | **18 - FL RTK** |
| **6 - IAC 1** | **19 - IL RTK** |
| **7 - IAC 2A** | **20 - LA RTK** |
| **8 - IARC 2B** | **21 - LA RTK** |
| **9 - OSHA** | **22 - MI 293** |
| **10 - OSHA Z** | **23 - MN RTK** |
| **11 - TSCA 4** | **24 - NJ RTK** |
| **12 - TSCA 5a2** | **25 - PA RTK** |
| **13 - TSCA 5e** | **26 - RI RTK** |

Code Key:
CAN2 = Carcinogen
SG1 = Suspected Carcinogen

## SECTION 16. OTHER INFORMATION

| | |
|---|---|
| **Use** | Lubricant |

| Ingredient | Percent | CAS Number |
|---|---|---|
| Paraffinic Extract | >70 | 64742-52-4 |
| Additives/Thickener | <15 | 9016-01-6 |

## SECTION 17. DISCLAIMER

Note: products do not contain PCBs.

Information given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability for use are beyond our control and therefore all warranties, express or implied, arising by law or otherwise, including any and all warranties of merchantability and fitness for a particular purpose, are expressly excluded. Nothing herein shall be taken as permission, recommendation or inducement to use any product in a manner which may infringe existing patent rights. Health hazards may exist for unsolicited products which are not mentioned herein. Buyer should determine the suitability of the product for its intended use and buyer assumes all risks and liability whatsoever in connection therewith, including risks not specifically identified herein. The information given herein relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

FIRST AID: Wash skin with soap and water. Flush eyes with water. If exercise to fumes or vapour, remove to fresh air. If ingested do not induce vomiting. If symptoms persist seek medical attention. Read and understand the MSDS before using this product.

INJECTION INJURY WARNING: If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a surgeon. High pressure injection, even with apparently minor wounds, can result in serious damage, including the need for amputation. Remember to tell emergency personnel where the fluid has been injected, because they may need to know this to ensure proper treatment.

SAFETY: Under normal conditions of intended use, this product does not pose a risk to health. Excessive exposure may result in eye, skin or respiratory irritation. Always observe good hygiene measures.

DISCLAIMER
Information given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of the product for particular uses are beyond our control and therefore all warranties of note of use of the product, express or implied, arising by law or otherwise, including any and all warranties of merchantability and fitness for a particular purpose or treason to the use or suitability of the product.
Nothing herein shall be taken as permission, recommendation or inducement to use any product in a manner which may infringe existing patent rights. Appropriate warnings and safe handling procedures should be provided to handlers and users.

Nothing is intended as a recommendation for uses, which infringe valid patents, or as extending license under valid patents. Appropriate warnings and safe handling procedures should be provided to handlers and users.

| | |
|---|---|
| **Prepared by** | NOVA INDUSTRIAL CC<br>Product Technical Services |
| **For further information Please contact:** | Technical manager:<br>Tel: 011 444 8000<br>Fax: 011 444 8006 |