PRECISION
LUBRICATION



15W30 HEAVY DUTY ULTRA GUARD

Description

SAE 15W30 is a high-performance multigrade engine oil formulated for use in a wide range of diesel and gasoline engines. It provides excellent protection against wear, oxidation, and sludge formation while maintaining optimal viscosity across a broad temperature range. Suitable for both naturally aspirated and turbocharged engines operating in moderate to warm climates.

Applications

Recommended for use in heavy duty four stroke turbocharged and naturally aspirated diesel engines both on and off highway. Also suitable for gasoline engines in passenger cars, light trucks and vans. Ideal for mixed fleet operations where a single oil grade is preferred for convenience. Suitable for use with low and high sulphur diesel fuels.

Features/Benefits

Satisfies the majority of engine requirements in SA
Extended drain capability – suitable for both high and low sulphur fuels
Excellent thermal and oxidative stability
Provides outstanding wear protection
Effective sludge and varnish control
Suitable for mixed fleet operations

TYPICAL CHARACTERISTICS

TEST	TYPICAL RESULTS
Sae no	15W-30
Viscosity cst @40°C cst @ 100°C	95 11.5
Viscosity Index	140
Flash Point °C	215
Pour Point ^{0}C	-30
Total Base No, mgKOH/g	9.5
Sulphated Ash, % m/m	1.2

Note : Ensure adequate re-lubrication intervals are carried out according to working temperature ranges used.

DISCLAIMER: The information given in this document is offered in good faith, but no warranty is implied or expressed. The onus is on the end user to ensure the suitability of this product to meet the end user requirements. It is also the end user's responsibility to follow health & safety procedures when using this product.

