PRECISION LUBRICATION

MATERIAL SAFETY DATA SHEET

Product Name	20W50 SYCATA Heavy Duty ULTRA GUARD
Product Code	
Symbols	Not Classified
Labelling for Transport	Not Classified

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name	20W50 SYCATA Heavy Duty ULTRA GUARD
Supplier	NOMA INDUSTRIAL CC
Updated	Apr. 2023
Review	April 2025
CAS Number	N/A
UN Number	N/A
Health Emergency Telephone	2075 - Red Cross Poison
Transport Emergency Telephone	(011) 331 2967 (Hazchem)

A petroleum product. DMSO extract < 3 (IP 346)

SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients considered hazardous to Health:

Mixtures Distillates (petroleum) solvent-dewaxed heavy paraffinic		60-100%
CAS number: 64742-65-0	EC number: 265-169-7	REACH registration number: 01-2119471299-27-XXXX

SECTION 3. HAZARDOUS IDENTIFICATION

US OSHA Hazard communication Standard	Product assessed in accordance with OSHA 29 CFR 1910.1200 and determined not to be hazardous.
Note	Keep good personal hygiene and avoid prolonged exposure.
Emergency Response Data	Lubricating Grease
Note:	Under normal conditions of intended use, this product does not pose a risk to health. Excessive exposure may result in eye, skin and respiratory irritation.

See Section 11 for further health effects/toxicological data.

SECTION 4. FIRST AID MEASURES

Inhalation	Not expected to be a problem. However, if respiratory irritation occurs due to excessive vapour or mist exposure, seek immediate medical assistance. If breathing has stopped, trained personnel should administer artificial respiration or oxygen by mouth-to-mouth resuscitation.
Skin	Remove contaminated clothing. Dry wipe exposed skin and cleanse with hand cleaner, soap and water. Launder contaminated clothing before reuse. Seek medical help if irritation occurs.
Eyes	Flush thoroughly with water. If irritation occurs, get medical assistance.
Ingestion	Not expected to be a problem. However, if discomfort occurs seek medical attention. Do not induce vomiting.

SECTION 5. FIRE FIGHTING MEASURES

Extinguishing media	Carbon dioxide, fire, dry chemical and water fog.
Special Fire-fighting procedures	Water or hose may cause frothing. Use water to keep fire exposed containers cool. Do not allow run-off from fire fighting to enter drains or watercourse. Prevent run-off from fire control or dilution from entering streets, municipal sewers, or drinking water supply.
Special protective equipment	For fires in enclosed areas, fire fighters must use Self-Contained Breathing Apparatus.
Unusual fire and explosion hazards	None.
Products of decomposition	Fumes, smoke, carbon monoxide, sulphur oxides, aldehydes and other decomposition products. In the case of incomplete combustion.
Flashpoint C	> 199 °C (ASTM D-92)

NFPA Hazard ID:

Health	0
Flammability	1
Reactivity	0
Hazardous decomposition products	Carbon Dioxide Carbon Monoxide

SECTION 6. ACCIDENTAL RELEASE MEASURES

Notification procedures	Report spills/releases as required to appropriate authorities.
Procedures if the materials is released or spilled	Wipe off excess during normal safety precautions. Take measures to minimise spillage entering drains or watercourse. Absorb in vermiculite, dry sand or equipment or cotton quilted liquid with sand or other suitable absorbent and remove mechanically into containers.
Environmental precautions	Prevent spillage from entering storm sewers or drains and contact with soil.
Personal precautions	See Section 13

SECTION 7. HANDLING AND STORAGE

Handling	No special precautions are necessary beyond normal good hygiene practices during handling. Avoid contact with skin and eyes.
Storage	Keep containers closed when not in use. Do not store in open or unlabelled containers. Keep away from heat, sparks, flame, ignition sources. Radiate strong oxidising agents and combustible materials.
Storage and handling procedures	Prevent small spills and leakages to avoid slip hazard.

SECTION 8. EXPOSURE CONTROL/PERSONAL PROTECTION

Occupational exposure limits Distillates (petroleum) solvent-dewaxed heavy paraffinic
Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.
Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield.

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. Wear protective gloves made of the following material: Nitrile rubber. Polyvinyl chloride (PVC).
Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. Wear protective gloves made of the following material: Nitrile rubber. Polyvinyl chloride (PVC).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid
Colour	Amber
Odour	Mild
pH	N/A
Boiling Point (Celcius)	N/A
Flash Point	> 220 °C (ASTM D-92)
Flammability	Flammable
Auto Flammability	N/A
Explosive Properties	N/A
Oxidising Properties	N/A
Vapor pressure mmHg 20OC	< 0.1 kPa
Density at 20°C	0.887g/cm3 @ 15 °C (ASTM D-4052)
Viscosity	159 cst @40°C

N/A = Not Applicable, N/D = Not Established, D = Decomposes
For further technical information, contact your nearest representative

SECTION 10. STABILITY AND REACTIVITY

Reactivity	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	The product is stable.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	Extreme heat and high energy sources of ignition, such as sparks and static electricity.
Incompatible materials	Strong oxidizers
Hazardous decomposition products	Fumes, smoke, carbon monoxide, sulphur oxides, aldehydes and other decomposition products. In the case of incomplete combustion.

SECTION 11. TOXICOLOGICAL INFORMATION

Oral toxicity	Practically non-toxic (LD50: Greater than 2000 mg/kg). Based on testing of similar products and/or components.
Dermal toxicity	Practically non-toxic (LD50: Greater than 2000 mg/kg). Based on testing of similar products and/or the components.
Inhalation toxicity	Practically non-toxic (LC50: greater than 5mg/l). Based on testing of similar products and/or the components.
Eye irritation	Practically non-irritating. (Draize score: greater than 0 but 15 or less). Based on testing of similar products and/or the components.
Skin irritation	Practically non-irritating. (Primary irritation index: greater than 0.5 but less than 2). Based on testing of similar products and/or the components.
Other toxicity data	Although an acute inhalation study was not performed with this product, a vapour/mist aerosol test method, such as those in the ASTM D4950, have been tested. These samples fail virtually to affect other than a transient irritation to the upper airways of the rat. Based on experience with the like presence of additives in other tested formulations at approximately the same concentrations, this product is not expected to cause irritation to the eyes effects. Overexposure to oil mist may result in of droplet deposition and/or granuloma formation.
Sensitization:	Not expected to be sensitizing based on tests of this product, components, or similar products.
Repeated dose toxicity	No significant adverse effects were found in studies using repeated dermal application of similar petroleum base oils to rabbits for 90 days and to rats for 2 weeks at doses significantly higher than those expected during normal industrial exposure. The animals were evaluated extensively for effects of systemic toxicity, including clinical signs, body weight, food intake, and microscopic examination of tissues and organs. Repeated exposure to petroleum base oils has also been shown irritation to the skin, eyes or respiratory tract.
Teratogenicity	No teratogenic effects would be expected from dermal exposure, based on laboratory developmental toxicity studies of major components in this formulation and/or similar oil-based formulations.
Carcinogenicity	Chronic mouse skin painting studies of severely solvent refined mineral base oils have produced evidence of carcinogenicity. These highly refined oils have been tested in the Ames assay and other tests of mutagenicity with negative results. These base oils are not expected to be carcinogenic with chronic skin contact exposure.

SECTION 12. ECOLOGICAL INFORMATION

Biodegradability	This product is expected to be inherently biodegradable
Physico-chemical Removability	Absorption to sediment and soil will not be the predominant behaviour.
Bioaccumulation	Minimal owing to low water solubility
Ecotoxicity effects	
Toxicity to aquatic organisms	This substance is practically non-toxic to aquatic organisms (LL/EL >1000 mg/L).

Further information on ecology

Remarks	In the absence of specific environmental data for this product, this assessment is based on information for representative substances.

SECTION 13. DISPOSAL INFORMATION

Waste disposal Product is suitable for burning in an enclosed, controlled burner for fuel value or disposal by supervised incineration. Such burning may be limited pursuant to the Resource Conservation and Recovery Act. In addition, the product should only be burned after approval by state and local authorities. Do not burn unless a government approved waste disposal facility is available. Use of these methods is subject to user compliance with applicable laws and regulations and consideration of product characteristics at time of disposal.

Contaminated packaging Empty containers retain residue (liquid and/or vapour) and can be dangerous. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Do not attempt to clean containers since residue is difficult to remove. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

Other regulations The unused product, in our opinion, is not specifically listed by the EPA as a hazardous waste (40 CFR, Part 261d), nor is it formulated to contain materials which are listed hazardous wastes. It does not exhibit the hazardous characteristics of ignitability, corrosivity, or reactivity and is not formulated with contaminants as determined by the Toxicity Characteristic Leaching Procedure (TCLP). However, used product may be regulated.

Dispose of waste at an appropriate waste disposal facility in accordance with current applicable laws and regulations, and product characteristics at time of disposal.

Flash Point > 189 °C (ASTM D-92).

SECTION 14. TRANSPORT INFORMATION

This product is not regulated by the following: U.S. DOT (CFR), ADR, IATA and IMDG.

SECTION 15. REGULATORY INFORMATION

US OSHA Hazard
Communication Standard: When used for its intended purposes, this product is not classified as hazardous in accordance with OSHA 29 CFR 1910.1200.

Governmental Inventory
Status: All components comply with TSCA, EINECS/ELINCS, AICS, METI, DSL, KECI, ENCS, PICCS and IECSC.

EU Labelling: Product is not dangerous as defined by the European Union Dangerous Substances/ Preparations Directives. EU labelling not required.

SARA

U.S. Superfund This product contains no "EXTREMELY
Amendments and HAZARDOUS SUBSTANCES".
Reauthorization Act SARA
Title III
SARA (311/312) Reportable
Hazard Categories: None

The following product ingredients are cited on the lists below

Chemical Name	CAS Number	List Citations
Paraffinic Extract	64742-54-7	117

Regulatory list searched

1 = ACGIH ALL
2 = ACGIH A1
3 = ACGIH A2
4 = NTP
5 = NTP A
6 = IARC 1
7 = IARC 2A
8 = IARC 2B
9 = OSHA
10 = OSHA 2
11 = TSCA 4
12 = TSCA 5a2
13 = TSCA 5e

Code Key:
CARC = Carcinogen
5a5 = Suspected Carcinogen

SECTION 16. OTHER INFORMATION

Use	Lubricant

Ingredient	Percent	CAS Number
Paraffinic Extract	>75	64742-54-7
Additive/Thickener	<15	8016-01-6

SECTION 17. DISCLAIMER

Note: products do not contain PCBs.

Information given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of the product for particular uses are beyond our control. We user therefore assumes all risks of use of the product. Remedies are limited to the purchase price or replacement. No statements or recommendations are to be inferred from or for a particular purpose in respect to the use or suitability of the product.

Health studies have shown that many lubricants pose potential human health risks which may vary from person to person. Information provided on this MSDS reflects conditions of current use. This product should not be used for any other applications. In any case, the following advice should be considered:

AVOIDING CONTACT: Used engine oil may contain harmful combustion by-products, which may be absorbed through the skin. Avoid prolonged or repeated contact with used engine oil. Use protective clothing and gloves. Wash skin thoroughly with soap and water. Use a nail brush if necessary. Do not use petrol, thinners or solvents to clean skin. Apply a skin cream after washing. Do not wash your hands in petrol, diesel fuel, or other solvents. Avoid contaminating clothes with used engine oil. Do not keep oily rags in your pocket. Remove clothing wet with oil and wash before reuse. Clothing that cannot be cleaned should be destroyed. Do not put oily rags in pockets or carry them next to the skin. Avoid skin contact with used engine oil. Do not use used engine oil as a general purpose skin cleaner. Do not put used engine oil in food containers.

PROTECTIVE ACTION: Wear protective clothing and gloves. Use a barrier cream. Avoid splashing or misting. Use in a well ventilated area. Keep sparks and flames away. Do not smoke.

DISPOSAL: Dispose of used engine oil only at authorised disposal sites. Do not pour into drains, waterways or onto the ground. Do not burn used engine oil in other than specially designed burners.

FIRST AID: Wash skin thoroughly with soap and water or use a recognised skin cleanser. Remove oil-soaked clothing. Obtain medical attention if irritation persists. Wash clothing before reuse. Clean shoes thoroughly before reuse. Discard oil-soaked shoes. Do not inject into or under the skin or into any part of the body, regardless of the appearance of the wound or its size. The individual should be evaluated immediately by a doctor in a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

EYE CONTACT: Under normal conditions of intended use, this product does not pose a risk to health. Excessive exposure may result in eye, skin or respiratory irritation. Avoid repeated or prolonged contact with oil. Wear safety glasses where there is any possibility of eye contact. Flush eyes with plenty of water. Seek medical attention if irritation occurs.

DISCLAIMER
Information given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of the product for particular uses are beyond our control. We user therefore assumes all risks of use of the product. Remedies are limited to the purchase price or replacement. No statements or recommendations are to be inferred from or for a particular purpose in respect to the use or suitability of the product.
Nothing is intended as a recommendation for uses which infringe valid patents, or as extending license under valid patents. Appropriate warnings and safe handling procedures should be provided to handlers and use.

Nothing is intended as a recommendation for uses, which infringe valid patents, or as extending license under valid patents. Appropriate warnings and safe handling procedures should be provided to handlers and use.

Prepared by	NOMA INDUSTRIAL CC Product Technical Services

For further information Please contact:	Technical manager: Mr. Ian Noma Tel. 011 849 8000