PRECISION LUBRICATION

MATERIAL SAFETY DATA SHEET

Product Name	HYDRAULIC 10 HEAVY DUTY HYDRO CARE
Product Code	
Symbols	Not Classified
Labelling for Transport	Not Classified

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name	Hydraulic 10 Heavy Duty HYDRO CARE
Supplier	NONA INDUSTRIAL CC
Updated	April 2021
Review	April 2023
CAS Number	N/A
UN Number	N/A
Health Emergency Telephone	Fire - Red Cross Poison
Transport Emergency Telephone	(011) 331 2947 (Hechett)

SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures Distillates (petroleum) solvent-dewaxed heavy paraffinic
EC-NO%
CAS number: 64742-65-0
EC number: 265-169-7
REACH registration number: 01-2119471299-27-XXXX

A petroleum product. Extract w/wt = 3 % weight (IP 346)
Classification (67/548/EEC or 1999/45/EC):
Not Classified

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition comments: If REACH registration numbers do not appear the substance is either exempt from registration or below the tonnage threshold for registration, the registration date has not yet come due or this information is proprietary.

SECTION 3. HAZARDOUS IDENTIFICATION

US OSHA Hazard communication Standard	Product assessed in accordance with OSHA 29 CFR 1910.1200 and determined not to be hazardous.
Note	Keep good personal hygiene and avoid prolonged exposure.
Emergency Response Data	Lubricating Grease

SECTION 4. FIRST AID MEASURES

Inhalation	Not expected to be a problem. However, if respiratory irritation occurs due to excessive vapour or mist exposure, seek immediate medical assistance. If breathing has stopped, assist ventilation with mechanical device or use mouth-to-mouth resuscitation.
Skin	Remove contaminated clothing. Dry wipe exposed skin and cleanse with soap and water. Seek medical attention if irritation persists. Before reuse (See Section 7). Injection Injury
Eyes	Flush thoroughly with water. If irritation occurs call a doctor.
Ingestion	Not expected to be a problem. However, if discomfort occurs seek medical attention. Do not induce vomiting.

SECTION 5. FIRE FIGHTING MEASURES

Extinguishing media	Carbon dioxide, foam, dry chemical and water fog.
Special Fire-fighting procedures	Water or foam may cause frothing. Use water to keep fire exposed containers cool. Avoid breathing fumes, smoke or vapour. Avoid exposure. Protect yourself from fire control or dilution from entering streams, sewers or drinking water supply.
Special protective equipment	For fires in enclosed areas, fire fighters must use Self-Contained Breathing Apparatus.
Unusual fire and explosion hazards	Fumes, smoke, carbon monoxide, sulphur oxides, aldehydes and other decomposition products, in the case of incomplete combustion.
Products of decomposition	> 199 °C (ASTM D 92).
Flashpoint C	

NFPA Hazard ID

Health	0
Flammability	1
Reactivity	0
Hazardous decomposition products	Carbon Dioxide Carbon Monoxide

SECTION 6. ACCIDENTAL RELEASE MEASURES

Notification procedures	Report spill as required to appropriate authorities.
Methods for cleaning up	LAND SPILL: Shut off source taking normal safety precautions. Take measures to minimize the effects on the ground water. Recover by pumping using explosion-proof equipment or contain spilled liquid with sand or other inert absorbent material. Place in suitable containers for treatment. If necessary dispose of absorbed residues as directed in Section 13.
Environmental precautions	Prevent spills from entering storm sewers or drains and contact with soil.
Personal precautions	See Section 13

SECTION 7. HANDLING AND STORAGE

Safe handling advice	No special precautions are necessary beyond normal good hygiene practices.
Storage information	Keep containers closed when not in use. Do not store in open or unlabelled containers. Do not store near heat sources, sparks, flame, strong oxidising agents and combustible materials.
Storage and handling procedures	Prevent small spills and leakages to avoid slip hazard

SECTION 8. EXPOSURE CONTROL/PERSONAL PROTECTION

Occupational exposure limits Distillates (petroleum) solvent-dewaxed heavy paraffinic

LTEL:
Long Term Exposure Limits - Time Weight Average (TWA) over 8 hours.

STEL:
Short Term Exposure Limits - Time Weight Average (TWA) over 15 Minutes

Note:
Limits Shown for guidance only. Follow applicable regulations.

2-ethylhexyl ster (CAS: 4259-15-8)

DNEL
- Workers - Dermal; systemic effects: 0.14 mg/kg/day
- Workers - Inhalation; systemic effects: 0.422 ppm
- Workers - Inhalation; Long term systemic effects: 0.07 ppm
- Workers - Inhalation; local effects: 0.09 mg/cm²
- Workers - Inhalation; local effects: 0.42 ppm
- Workers - Inhalation; Long term systemic effects: 0.21 ppm
- Workers - Dermal; Long term systemic effects: 0.09 mg/cm²
- Workers - Dermal; Long term systemic effects:

PNEC
- Fresh water: 0.004 mg/l
- Soil: 0.0548 mg/kg
- Fresh water (Intermittent): 0.0701 mg/kg
- Marine water: 0.0046 mg/l
- Sediment (Marinewater): 0.00701 mg/kg
- STP: 3.8 mg/l
- Air: 71 mg/m³

benzenesulfonic acid, mono-C16-24-alkyl derivs.

DNEL
- Workers - Dermal; Long term systemic effects: 3.33 mg/kg
- Workers - Inhalation; Long term systemic effects: 0.46 mg/m³
- Consumer - Dermal; Long term systemic effects:
- Consumer - Inhalation; Long term systemic effects: 0.33 mg/m³
- Consumer - Oral; Long term systemic effects:

PNEC
- Fresh water; 1 mg/l - Soil: 0.667000000 mg/kg
- Sediment (Freshwater): 7.235000000 mg/kg
- STP: 100 mg/l - Marine water; 1 mg/l
- Intermittent release; 10 mg/l
- Sediment (Marinewater): 72.350000000 mg/kg

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid
Colour	Light Amber
Odour	Mild
pH	N/A
Boiling Point (Celsius)	> 300 °C
Flash Point	> 190 °C (ASTM D 92).
Pour Point	10 °C
Flammability	Flammable
Auto Flammability	N/E
Explosive Properties	N/A
Oxidising Properties	N/A
Vapour pressure	< 0.1 kPa
Density at 25°C	0.874 g/cm3 @ 25 °C (ASTM D 4052)
Solubility in water	Negligible

N/A = Not Applicable, N/E = Not Established, D = Decomposes
For further technical information, contact your marketing representative

SECTION 10. STABILITY AND REACTIVITY

Stability	Stable
Conditions to avoid	Extreme heat and high energy sources of ignition, such as sparks and static electricity.
Materials to avoid	Strong oxidizers
Hazardous decomposition products	Fumes, smoke, carbon monoxide, sulphur oxides, aldehydes and other decomposition products, in the case of incomplete combustion

SECTION 11. TOXICOLOGICAL INFORMATION

Oral toxicity	Practically non-toxic (LD50, greater than 2000mg/kg). Based on testing of similar products and/or the components.
Dermal toxicity	Practically non-toxic (LD50, greater than 2000 mg/kg). Based on testing of similar products and/or the components.
Inhalation toxicity	Not established.
Eye irritation	Practically non-irritating. Based on testing of similar products and/or the components.
Other acute toxicity data	Practically non-irritating. Based on testing of similar products and/or the components.
Sensitization	Not expected to be sensitizing based on tests of this product, components, or similar products.
Repeated dose toxicity	No significant adverse effects were found in studies using repeated dermal applications of similar formulations to the skin of laboratory animals for 13 weeks at doses significantly higher than those expected during normal handling conditions. Effects noted in these studies include mild changes in exposure dermatology, serum chemistry, urinalysis, organ weights, microscopic examination of tissues etc.). Prolonged skin contact may cause irritation to the skin, eyes or respiratory tract.
Teratogenicity	No teratogenic effects would be expected from dermal exposure, based on relevant developmental toxicity studies of major components in this product. Based on testing of similar products.
Carcinogenicity	Chronic mouse skin painting studies of severely solvent refined mineral base oils of comparable viscosity to those used in this product have been shown to have tested in the Ames assay and other tests of mutagenicity with negative results. This product is not expected to be carcinogenic with chronic dermal exposure.

SECTION 12. ECOLOGICAL INFORMATION

Environmental fate and effects	Not established.
Biodegradability	This product is expected to be inherently biodegradable.
Physico-chemical Removability	Absorption to sediment and soil will be the predominant behaviour.
Bioaccumulation	Minimal owing to low water solubility
Toxicity to aquatic organisms	This substance is practically non-toxic to aquatic organisms (LL50 >1000 mg/l)
Further information on ecology	In the absence of specific environmental data for this product, this assessment is based on data for representative substances.

SECTION 13. DISPOSAL INFORMATION

Waste disposal:
Product is suitable for burning in an enclosed, controlled burner for fuel value or disposal by supervised incineration. Such burning may be

subject to regulation by the U.S. Environmental Protection Agency and the Resource Conservation and Recovery Act. In addition, this product is suitable for processing by an approved recycling facility or can be disposed of at any government approved waste disposal facility. Use of these methods is subject to user compliance with applicable laws and regulations and considerations of product characteristics at time of disposal.

Contaminated packaging:
Empty containers retain residue (liquid and/or vapour) and can be dangerous. **DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.** Do not attempt to refill or clean container since residue is difficult to remove. Empty drums should be completely drained and properly bunged and promptly conveyed to a drum reconditioner. Containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

Other regulations:
Not classified as hazardous waste. In addition, it is not specifically listed by the EPA as a hazardous waste (40 CFR, Part 261), nor is it formulated to contain materials which are listed hazardous wastes. It does not exhibit the hazardous characteristics of ignitability, corrosivity, or reactivity and is not formulated with contaminants as determined by the Toxicity Characteristic Leaching Procedure (TCLP). However, used product may be regulated.

Flash Point: > 189 °C (ASTM D-92)

SECTION 14. TRANSPORT INFORMATION

Note: This product is not regulated by the following: U.S. DOT (CFR), ADR, IATA and IMDG.

SECTION 15. REGULATORY INFORMATION

US OSHA Hazard
Communication Standard. When used for its intended purposes, this product is not classified as hazardous in accordance with OSHA 29 CFR 1910.1200.

Governmental Inventory
Notice: All components comply with TSCA, EINECS/ELINCS, AICS, METI, DSL, KECI, ENCS, PICCS and IECSC.

EU Labelling: Product is not dangerous as defined by the European Union Dangerous Substances' Preparations Directives. EU labelling not required.

SARA

U.S. Superfund This product contains no "EXTREMELY Amendments and HAZARDOUS SUBSTANCES". Reauthorization Act SARA

Title III
SARA (311/312) Reportable
Hazard Categories: None

The following product ingredients are cited on the lists below

1 - ACGIH ALL	**11 - TSCA 4**
2 - ACGIH A1	**12 - TSCA 5a2**
3 - ACGIH A2	**13 - TSCA 5e**
4 - NTP	**14 - TSCA 6**
5 - NTP A	**15 - TSCA 12b**
6 - IAC 1	**16 - CA P65**
7 - IAC 2A	**17 - CA RTK**
8 - IARC 2B	**18 - FL RTK**
9 - OSHA	**19 - IL RTK**
19 - IL RTK	**20 - LA RTK**

Code Key:
CARC = Carcinogen
SUS = Suspected Carcinogen

SECTION 16. OTHER INFORMATION

Use	Lubricant

Ingredient	**Percent**	**CAS Number**
Synthetic Extract	>70	63461-82-8
Additives/Thickener	<15	61789-07-8

SECTION 17. DISCLAIMER

Note: products do not contain PCBs.

Health studies have shown that many hydrocarbons pose potential human health risks which may vary from person to person. Information provided on this MSDS reflects reasonable and prudent practices, but is not intended to be all-inclusive nor adapted to specific applications. In any case, the following advice should be considered:

FIRST AID: Wash skin with soap and water. Flush eyes with water. If swallow by turbine or vapour, remove to fresh air. Seek medical attention if symptoms persist. Keep victim warm and quiet. Do not induce vomiting. Avoid over-exposure. Read and understand the MSDS before using this product.

INJECTION INJURY WARNING: If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a surgeon. It is important to realize that a very serious injury may not be painful initially or have only a minor appearance. Do not delay. Time is of the essence. Failure to explain the injection to the physician can result in an amputation of the affected finger, hand or arm or even a loss of life. Early surgical exploration and debridement of the injection site may prevent subsequent serious infection.

SAFETY: Under normal conditions of intended use, this product does not pose a risk to health. Excessive exposure may result in eye, skin or respiratory irritation. Wear chemical goggles if splashing is expected.

DISCLAIMER
The information given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of the product for particular uses are beyond our control and, therefore, we disclaim any liability for loss or injury which may arise from the use of this product and we expressly disclaim all warranties of every kind and nature, including warranties of merchantability and fitness for a particular purpose, whether arising by law, custom, or conduct.

Nothing in this material is recommended for use in violation of patent rights of others, nor as an indemnity license under same patents. Appropriate warnings and safe handling procedures should be provided to handlers and users.

Prepared by	NONA INDUSTRIAL CC Product Technical Services

For further information Please contact:
Technical Manager
Nona CC
Tel: 011 944 8659