

## SANEG PREMIUM DEX 5W-30

SANEG Premium DEX 5W-30 is advanced performance totally synthetic engine oil developed to meet or exceed the toughest international standards of main American and Asian manufacturers of newest gasoline-fueled vehicles. It provides exceptional wear protection and outstanding performance to compact, high-power engines with technologies such as gasoline direct injection (GDI) and turbocharging. It improves fuel efficiency, meeting stringent fuel economy and emissions requirements.

### APPLICATIONS

High-performance turbo-charged, supercharged, direct injection gasoline engines of passenger cars, light trucks and vans, equipped (or not) with catalytic converter and/or particulate filter. Specifically for General Motors and Japanese and Korean vehicles where a SAE 5W-30 viscosity grade and any of its service classifications are recommended. Oils formulated to meet the Gen 3 specification are backwards compatible for vehicles that require Gen2.

### PERFORMANCE

Outstanding protection against wear and deposits under all operating conditions including frequent short trips or idling, or extreme temperature environment  
 High turbocharger protection and fuel efficiency  
 Very high performance upon cold temperature operation and low-speed pre-ignition (LSPI) prevention, an issue that can cause damage to newer engines  
 Excellent oxidation resistance to fight against oil degradation and deposit formation  
 Very good detergent and dispersant properties for excellent engine cleanliness

### SPECIFICATIONS

API SP-RC, ILSAC GF-6A  
 GM DEXOS 1 GEN 3

Property	Method	SANEG PREMIUM DEX 5W-30
Kinematic Viscosity @40°C, mm <sup>2</sup> /s	ASTM D445	71,3
Kinematic Viscosity @ 100°C, mm <sup>2</sup> /s	ASTM D445	12,10
Viscosity Index	ASTM D2270	168
Flash Point (COC), °C	ASTM D92	225
Pour Point, °C	ASTM D97	-42
Density @ 15°C, kg/l	ASTM D1298	0,850

Product information is contained in the relevant safety data sheet (SDS). This sheet provides guidance on potential hazards, precautions and first aid measures, together with environmental effects and disposal of used products. SDSs are available upon request from the sales office. This product must not be used for any purpose other than its intended use. Edition 01/2025