SANEG PREMIUM 10W-40

SANEG Premium 10W-40 is an engine oil formulated with mineral and synthetic base components and a composition of specially selected additives to ensure a resistant lubricating film and protection against engine wear on motorway routes and in city driving.

APPLICATIONS

Petrol and diesel engines without particulate filters in passenger cars, SUVs, light trucks and vans

PERFORMANCE

Good detergent-dispersant properties and protection against deposit formation
Excellent engine cleanliness and high thermal stability
Reliability and operating efficiency of the engine
Protection against wear thanks to the resistance of the lubricating film at high temperatures

SPECIFICATIONS

API SL/CF

Property	Method	SANEG PREMIUM 10W-40
Kinematic Viscosity @40°C, mm^2/s	ASTM D445	93,70
Kinematic Viscosity @ 100°C, mm^2/s	ASTM D445	13,70
Viscosity Index	ASTM D2270	150
Flash Point (COC), °C	ASTM D92	225
Pour Point, °C	ASTM D97	-36
Density @ 15°C, kg/l	ASTM D1298	0,875

Product information is contained in the relevant safety data sheet (SDS). This sheet provides guidance on potential hazards, precautions and first aid measures, together with environmental effects and disposal of used products. SDSs are available upon request from the sales office. This product must not be used for any purpose other than its intended use. Edition 01/2025

SANEG OIL ITALY SPA
Via Francesco Benaglia 13
00153 Rome – Italy
Tel.: +39 06 83971600

While the information and data provided here is typical of current production and within specifications, minor variations may occur. If you need further information, consult our technical helpdesk.
E-mail: techinfo@saneg-oil.it