

SANEG EXTRA CNG-LPG 5W-30

SANEG Extra CNG-LPG 5W-30 is high performance totally synthetic engine oil developed to provide excellent protection of gas fueled engines of passenger cars under all operating conditions. Formulated with advanced technology Mid-SAPS additive system (reduced Sulfur, Phosphorus and Sulfated Ash content), it is compatible with exhaust gas after treatment systems such as Three Way Catalytic converters (TWC) and it provides outstanding performance in a wide range of temperatures.

APPLICATIONS

Passenger cars, light trucks and vans engines running on Compressed Natural Gas (CNG), Liquefied Petroleum Gas (LPG) and Dual Fuel (Gasoline + Gas), equipped (or not) with catalytic converter and/or particulate filter, requiring ACEA C3 or API SN/CF oil

PERFORMANCE

Outstanding protection against wear, corrosion, deposits formation and oil thickening under all operating conditions for long engine life
 Efficient operation of exhaust gas after treatment sensitive systems, preventing any damage of catalytic converter components
 Very good detergent and dispersant properties for excellent engine cleanliness
 Excellent thermal and oxidation stability

SPECIFICATIONS

ACEA C3
 API SN/CF

Property	Method	SANEG EXTRA CNG-LPG 5W-30
Kinematic Viscosity @40°C, mm ² /s	ASTM D445	69,44
Kinematic Viscosity @ 100°C, mm ² /s	ASTM D445	12,18
Viscosity Index	ASTM D2270	175
Flash Point (COC), °C	ASTM D92	229
Pour Point, °C	ASTM D97	-42
Density @ 15°C, kg/l	ASTM D1298	0,849

Product information is contained in the relevant safety data sheet (SDS). This sheet provides guidance on potential hazards, precautions and first aid measures, together with environmental effects and disposal of used products. SDSs are available upon request from the sales office. This product must not be used for any purpose other than its intended use. Edition 01/2025