

## SANEG EXTRA CNG-LPG 10W-40

SANEG Extra CNG-LPG 10W-40 is high performance semi-synthetic engine oil developed to provide excellent protection of gas fueled engines of passenger cars under all operating conditions. Formulated with advanced technology additive system, it provides protection against wear, corrosion, deposits formation and oil thickening in a wide range of temperatures.

### APPLICATIONS

Passenger cars, light trucks and vans engines running on Compressed Natural Gas (CNG), Liquefied Petroleum Gas (LPG) and dual fuel (Gasoline + Gas) requiring API SL/CF oil

### PERFORMANCE

Wear protection thanks to strong oil film under all operating conditions for long engine life  
Good detergent and dispersant properties for excellent engine cleanliness  
Resistance to sludge and harmful deposits under high temperature conditions  
Thermal and oxidation stability

### SPECIFICATIONS

API SL/CF

Property	Method	SANEG EXTRA CNG-LPG 10W-40
Kinematic Viscosity @40°C, mm <sup>2</sup> /s	ASTM D445	90,9
Kinematic Viscosity @ 100°C, mm <sup>2</sup> /s	ASTM D445	13,6
Viscosity Index	ASTM D2270	152
Flash Point (COC), °C	ASTM D92	226
Pour Point, °C	ASTM D97	-36
Density @ 15°C, kg/l	ASTM D1298	0,875

Product information is contained in the relevant safety data sheet (SDS). This sheet provides guidance on potential hazards, precautions and first aid measures, together with environmental effects and disposal of used products. SDSs are available upon request from the sales office. This product must not be used for any purpose other than its intended use. Edition 01/2025