



SANEG PREMIUM C2 0W-30

SANEG Premium C2 0W-30 is a fully synthetic high performance engine oil with fuel saving properties formulated to ensure maximum protection and performance of the highest performing engines that require ACEA C2 oil with reduced sulphated ash, sulphur and phosphorus content.

APPLICATIONS

High performance diesel and petrol direct injection turbo engines, with exhaust emission control systems (EGR, SCR, DPF, TWC) of cars, SUVs, light trucks and vans
 Petrol and diesel engines equipped with catalytic converters and particulate filters on cars and vans that require the ACEA C2 product and SAE 0W-30 viscosity, in particular Toyota, Nissan, Kia, Hyundai

PERFORMANCE

Energy and fuel saving properties
 Exceptional long-term performance without oil thickening due to oxidation and degradation
 High efficiency and long life of emission control systems such as the DPF (Diesel Particulate Filter)
 Excellent low temperature performance ensuring easy cold starts

SPECIFICATIONS

ACEA C2
 FORD WSS-M2C950-A
 FIAT 9.55535-GS1, FIAT 9.55535-DS1
 IVECO 18-1811 SC1 LV

Property	Method	SANEG PREMIUM C2 0W-30
Kinematic Viscosity @40°C, mm ² /s	ASTM D445	56,3
Kinematic Viscosity @ 100°C, mm ² /s	ASTM D445	11,7
Viscosity Index	ASTM D2270	209
Flash Point (COC), °C	ASTM D92	215
Pour Point, °C	ASTM D97	-45
Density @ 15°C, kg/l	ASTM D1298	0,843

Product information is contained in the relevant safety data sheet (SDS). This sheet provides guidance on potential hazards, precautions and first aid measures, together with environmental effects and disposal of used products. SDSs are available upon request from the sales office. This product must not be used for any purpose other than its intended use. Edition 01/2025