

SANEG PREMIUM PLUS 10W-40

SANEG Premium Plus 10W-40 is an engine oil formulated with mineral and synthetic base oils and an additive technology able of ensuring excellent cleaning and anti-wear protection of the engine on motorway routes and in city driving.

APPLICATIONS

Petrol and diesel engines, aspirated or supercharged, especially turbodiesel engines with direct injection system, without particulate filters of cars, SUVs, light trucks and vans

PERFORMANCE

Excellent detergent-dispersant properties and protection against deposit formation
High resistance to oxidation and stability at high temperature for reliable operation even under severe operating conditions
Protection against wear thanks to the quick circulation of the oil in the engine at low temperatures during cold starts

SPECIFICATIONS

ACEA A3/B4
API SN/CF
MB 229.1
VW 505 00/501 01
RENAULT RN 0700

Property	Method	SANEG PREMIUM PLUS 10W-40
Kinematic Viscosity @40°C, mm ² /s	ASTM D445	97,50
Kinematic Viscosity @ 100°C, mm ² /s	ASTM D445	14,30
Viscosity Index	ASTM D2270	151
Flash Point (COC), °C	ASTM D92	231
Pour Point, °C	ASTM D97	-36
Density @ 15°C, kg/l	ASTM D1298	0,875

Product information is contained in the relevant safety data sheet (SDS). This sheet provides guidance on potential hazards, precautions and first aid measures, together with environmental effects and disposal of used products. SDSs are available upon request from the sales office. This product must not be used for any purpose other than its intended use. Edition 01/2025