

SANEG DIESEL PREMIUM PLUS CI-4 15W-40

SANEG Diesel Premium Plus CI-4 15W-40 is high performance engine oil designed to ensure maximum protection of heavy diesel engines in all operating conditions. It is formulated with high-quality base oils and a selected additive package that ensures excellent engine cleanliness and long life of components subjected to high loads.

APPLICATIONS

Heavy duty diesel engines of commercial vehicles and buses, quarry and construction equipment and agricultural machinery, with or without EGR and SCR
Suitable for petrol vehicle engines in mixed fleets requiring API SL motor oils
Not applicable for engines equipped with diesel particulate filters (DPF)

PERFORMANCE

Superior protection from engine wear
Excellent deposit control
Extended oil change intervals
High long-term engine performance
Excellent protection of bearings, rings and cylinders
Reduced oil consumption
Exceptional piston cleanliness and oxidation and soot control

SPECIFICATIONS

ACEA E7
API CI-4/SL
Caterpillar ECF-1a/ECF-2
Cummins CES 20077, CES 20078
Detroit Diesel DDC 93K215
Deutz DQC II, DQC III
JASO DH-1
Global DHD-1
MACK EO-N
MAN M 3275
MB 228.1, 228.3
MTU 2.0
Renault Trucks RLD-2
Volvo VDS-3

Property	Method	SANEG DIESEL PREMIUM PLUS CI-4 15W-40
Kinematic Viscosity @40°C, mm ² /s	ASTM D445	119,6
Kinematic Viscosity @ 100°C, mm ² /s	ASTM D445	15,35
Viscosity Index	ASTM D2270	134
Flash Point (COC), °C	ASTM D92	235
Pour Point, °C	ASTM D97	-33
TBN, mgKOH/g	ASTM D2896	11,5
Density @ 15°C, kg/l	ASTM D1298	0,882

Product information is contained in the relevant safety data sheet (SDS). This sheet provides guidance on potential hazards, precautions and first aid measures, together with environmental effects and disposal of used products. SDSs are available upon request from the sales office. This product must not be used for any purpose other than its intended use. Edition 01/2025