

SANEG DIESEL PREMIUM CI-4 15W-40

SANEG Diesel Premium CI-4 15W-40 is high performance engine oil that provides proven protection of heavy diesel engines operating in severe conditions for both on and off-highway applications. It is formulated with a selected additive package that ensures excellent engine protection against wear, deposits and overheating.

APPLICATIONS

Heavy duty diesel engines of commercial vehicles and buses, quarry and construction equipment and agricultural machinery, not applicable for engines equipped with diesel particulate filters (DPF)

PERFORMANCE

Excellent protection from engine wear in both low and high temperature service

Protection against corrosion from acidic products formed as fuel burns

Outstanding protection against oil thickening for extended drain intervals

Less high temperature deposits formation to reduce maintenance costs

SPECIFICATIONS

ACEA E7
API CI-4
MAN M 3275
MB 228.1, 228.3
Renault Trucks RLD-2
Volvo VDS-3

Property	Method	SANEG DIESEL PREMIUM CI-4 15W-40
Kinematic Viscosity @40°C, mm ² /s	ASTM D445	109,0
Kinematic Viscosity @ 100°C, mm ² /s	ASTM D445	14,5
Viscosity Index	ASTM D2270	136
Flash Point (COC), °C	ASTM D92	228
Pour Point, °C	ASTM D97	-33
TBN, mgKOH/g	ASTM D2896	10,0
Density @ 15°C, kg/l	ASTM D1298	0,886

Product information is contained in the relevant safety data sheet (SDS). This sheet provides guidance on potential hazards, precautions and first aid measures, together with environmental effects and disposal of used products. SDSs are available upon request from the sales office. This product must not be used for any purpose other than its intended use. Edition 01/2025