

## SANEG DIESEL EXTRA CF-4 15W-40

SANEG Diesel Extra CF-4 15W-40 is heavy duty diesel engine oil suitable for both on and off-highway applications. Maintains oil at optimal viscosity levels, ensuring optimal lubrication, reducing corrosion for longer engine life.

### APPLICATIONS

Heavy duty diesel engines of commercial vehicles and buses, quarry and construction equipment and agricultural machinery requiring API CF-4 quality

### PERFORMANCE

Good protection from engine wear and sludge build-up

Effective control on soot avoiding oil thickening

Helps reduce oil consumption and maintenance costs

### SPECIFICATIONS

API CF-4

Property	Method	SANEG DIESEL EXTRA CF-4 15W-40
Kinematic Viscosity @40°C, mm <sup>2</sup> /s	ASTM D445	111,70
Kinematic Viscosity @ 100°C, mm <sup>2</sup> /s	ASTM D445	15,10
Viscosity Index	ASTM D2270	140
Flash Point (COC), °C	ASTM D92	226
Pour Point, °C	ASTM D97	-30
TBN, mgKOH/g	ASTM D2896	6,3
Density @ 15°C, kg/l	ASTM D1298	0,882

Product information is contained in the relevant safety data sheet (SDS). This sheet provides guidance on potential hazards, precautions and first aid measures, together with environmental effects and disposal of used products. SDSs are available upon request from the sales office. This product must not be used for any purpose other than its intended use. Edition 01/2025