

## SANEG DRIVELINE ATF DX II

SANEG Driveline ATF DX II is high performance fluid for automatic transmissions that meets DEXRON®-II D requirements. It is formulated with an additive technology that ensures performance characteristics, friction and wear for smooth and reliable gear shifting.

### APPLICATIONS

High performance automatic and semi-automatic transmissions of passenger cars, on-road and off-road heavy-duty vehicles, requiring DEXRON® IID performance level  
Power steering systems and hydraulic applications where automatic transmission fluid is required

### PERFORMANCE

Excellent thermal and oxidation stability for maximum system cleanliness  
Good performance at low temperatures for easy shifting in cold conditions  
Excellent anti-wear properties for long transmission life  
Compatibility with common sealing materials and excellent leak control

### SPECIFICATIONS

Allison C-4  
Ford MERCON  
GM DEXRON® IID  
MAN 339 Type L2, V1, Z1  
MB 236.1  
Voith H55.6335  
ZF TE-ML 03D, 04D, 09, 14A, 17C

Property	Method	SANEG DRIVELINE ATF DX II
Kinematic Viscosity @40°C, mm <sup>2</sup> /s	ASTM D445	41,01
Kinematic Viscosity @ 100°C, mm <sup>2</sup> /s	ASTM D445	7,9
Viscosity Index	ASTM D2270	168
Flash Point (COC), °C	ASTM D92	205
Pour Point, °C	ASTM D97	-45
Density @ 15°C, kg/l	ASTM D1298	0,872
Colour	Visual	Red

Product information is contained in the relevant safety data sheet (SDS). This sheet provides guidance on potential hazards, precautions and first aid measures, together with environmental effects and disposal of used products. SDSs are available upon request from the sales office. This product must not be used for any purpose other than its intended use. Edition 01/2025