

## SANEG DRIVELINE ATF DX VI

SANEG DRIVELINE ATF DX VI is fully synthetic high performance automatic transmission fluid recommended for use in all types of latest generation automatic transmissions that require DEXRON VI fluid. It allows lower fuel consumption for cars equipped with automatic transmissions and ensure long service life under extreme operating conditions.

### APPLICATIONS

Latest generation automatic transmissions, transfer cases and power steering systems of American, Asian and European manufacturers that require DEXRON VI fluid  
Fully backwards compatible for use in automatic transmissions where DEXRON-II D and/or DEXRON-III H are recommended

### PERFORMANCE

Improved transmission efficiency and smooth shifting performance  
Excellent thermal and oxidation stability for reduced deposits and sludge build-up  
Outstanding transmission performance and long transmission life  
Excellent low temperature performance providing good cold-start shifting

### SPECIFICATIONS

Aisin Warner AW-1	Hyundai/Kia SP-IV
GM DEXRON-VI	Mitsubishi Diaqueen SP-IV
Honda ATF DW-1	Mitsubishi Diaqueen ATF PA
JASO M315-2013 1A-LV	Nissan Matic-S
Mazda ATF M-V/ ATF FZ	Toyota WS (JWS 3324)

Property	Method	SANEG DRIVELINE ATF DX VI
Kinematic Viscosity @40°C, mm <sup>2</sup> /s	ASTM D445	28,9
Kinematic Viscosity @ 100°C, mm <sup>2</sup> /s	ASTM D445	5,9
Viscosity Index	ASTM D2270	156
Brookfield Viscosity @-40°C, mPa·s	ASTM D2983	11300
Flash Point (COC), °C	ASTM D92	212
Pour Point, °C	ASTM D97	-45
Density @ 15°C, kg/l	ASTM D1298	0,848
Color		Red

Product information is contained in the relevant safety data sheet (SDS). This sheet provides guidance on potential hazards, precautions and first aid measures, together with environmental effects and disposal of used products. SDSs are available upon request from the sales office. This product must not be used for any purpose other than its intended use. Edition 01/2025