

## SANEG DRIVELINE ATF DX III

SANEG DRIVELINE ATF DX III is fully synthetic high performance automatic transmission fluid recommended for automatic transmissions of passenger cars and commercial vehicles, especially for the professional transport industry as long life oil. It allows an extension in drain intervals under even the most severe operating conditions, according to performance profile below, over a wide temperature range.

### APPLICATIONS

Automatic transmissions of passenger cars and commercial vehicles, where a product meeting DEXRON III requirements is recommended  
 Power steering systems and hydraulic applications where automatic transmission fluid is specified  
 Some manual transmissions where automatic transmission fluid is specified

### PERFORMANCE

Excellent thermal and oxidation stability for reduced deposits and sludge build-up  
 Outstanding transmission performance and long transmission life under severe driving conditions  
 Excellent low temperature performance providing good cold-start shifting  
 Enhanced friction properties for transmission high efficiency and smooth shifting performance  
 Compatible with all common seal materials and excellent leakage control

### SPECIFICATIONS

Allison C-4, TES-389&295  
 Ford MERCON V  
 GM DEXRON III H  
 MAN 339 Type L1/Z11/V2/Z2

MB 236.7  
 Voith H55.6336  
 Volvo 97340/97341  
 ZF TE-ML 04D/14B/16L/20B/25B

| Property  | Method     | SANEG DRIVELINE ATF DX III |
|---|------------|----------------------------|
| Kinematic Viscosity @40°C, mm <sup>2</sup> /s   | ASTM D445  | 40,0                       |
| Kinematic Viscosity @ 100°C, mm <sup>2</sup> /s | ASTM D445  | 7,9                        |
| Viscosity Index                                 | ASTM D2270 | 173                        |
| Brookfield Viscosity @-40°C, mPa·s              | ASTM D2983 | 15000                      |
| Flash Point (COC), °C                           | ASTM D92   | 202                        |
| Pour Point, °C                                  | ASTM D97   | -45                        |
| Density @ 15°C, kg/l                            | ASTM D1298 | 0,850                      |
| Color   |            | Red                        |

Product information is contained in the relevant safety data sheet (SDS). This sheet provides guidance on potential hazards, precautions and first aid measures, together with environmental effects and disposal of used products. SDSs are available upon request from the sales office. This product must not be used for any purpose other than its intended use. Edition 01/2025