

SANEG DRIVELINE GL-5 75W-90

SANEG Driveline GL-5 75W-90 is a high-performance semi-synthetic gear oil for gears operating under severe conditions including axles and final drives where high loads and extreme pressures are expected. Formulated with top quality mineral and synthetic base oils and a system of advanced technology additives, it ensures excellent resistance to high temperatures and maximum protection from wear, loads, foaming and corrosion.

APPLICATIONS

Transmissions, axles and differentials that require API GL-5 oil on cars and vans, commercial vehicles, buses and construction equipment
Not suitable for limited slip applications

PERFORMANCE

High load capacity for protection against low-speed/high-torque wear, high-speed scoring and spalling
Smooth shifting even in case of cold starting
Reduced deposits and sludge build-up for a long service life of final drives and axles
Very good shear stability and resistance to high temperature conditions
Compatibility with typical gaskets of the automotive sector

SPECIFICATION

API GL-5

Property	Method	SANEG DRIVELINE GL-5 75W-90
Kinematic viscosity @ 40°C, mm ² /s	ASTM D445	104
Kinematic viscosity @ 100°C, mm ² /s	ASTM D445	15,8
Viscosity index	ASTM D2270	162
Flash point COC, °C	ASTM D92	202
Pour Point, °C	ASTM D97	-42
Density @ 15°C, kg/l	ASTM D1298	0,862

Product information is contained in the relevant safety data sheet (SDS). This sheet provides guidance on potential hazards, precautions and first aid measures, together with environmental effects and disposal of used products. SDSs are available upon request from the sales office. This product must not be used for any purpose other than its intended use. Edition 01/2025