

## SANEG DRIVELINE GL-4 75W-80

SANEG Driveline GL-4 75W-80 is a totally synthetic mixed-fleet Premium Tier Manual Transmission Oil formulated with selected synthetic base oils and advanced top technology additive system, that provides extreme durability and fuel efficiency. Its performance profile covers 40% of commercial vehicle market.

### APPLICATIONS

Transmissions and transaxles requiring SAE 75W-80 oil with API GL-4 performance on cars and vans, commercial vehicles, buses and construction equipment  
 Manual and automatized mechanical ZF transmissions of heavy-duty vehicles, such as DAF, Iveco, Renault, requiring product with the profile of specifications below  
 Not suitable for limited slip applications

### PERFORMANCE

Easier shifting in cold climates while providing ultimate wear protection of manual transmission  
 Proper friction coefficient for correct synchronizer engagement  
 Reduced deposit and sludge formation for longer transmission life  
 Compatibility with typical seals in the automotive sector  
 Lower operating costs and maintenance periods  
 Reduced complexity and increased flexibility

### SPECIFICATIONS

API GL-4  
 MAN 341 TYPE Z4  
 ROBERT BOSCH TE-ML 08  
 VOLVO 97307  
 ZF TE-ML 01L/02L/13/16K

Property	Method	SANEG DRIVELINE GL-4 75W-80
Kinematic Viscosity @40°C, mm <sup>2</sup> /s	ASTM D445	54,90
Kinematic Viscosity @ 100°C, mm <sup>2</sup> /s	ASTM D445	9,60
Viscosity Index	ASTM D2270	160
Flash Point (COC), °C	ASTM D92	218
Pour Point, °C	ASTM D97	-42
Density @ 15°C, kg/l	ASTM D1298	0,856

Product information is contained in the relevant safety data sheet (SDS). This sheet provides guidance on potential hazards, precautions and first aid measures, together with environmental effects and disposal of used products. SDSs are available upon request from the sales office. This product must not be used for any purpose other than its intended use. Edition 01/2025