

SANEG DRIVELINE GL-5 85W-140

SANEG Driveline GL-5 85W-140 is high performance gear oil in severe service including axles and final drives subjected to extreme pressures and shock loads. Formulated with high-performance base oils and an advanced additive system, it provides excellent resistance to degradation and oil thickening at high temperatures, helping to keep bearing surfaces clean and minimize wear.

APPLICATIONS

Manual transmissions, axles and final drives in severe service requiring API GL-5 performance on cars, light and heavy-duty commercial vehicles, buses and vans, off-highway construction, quarrying and agricultural vehicles

PERFORMANCE

Excellent EP properties and gear wear protection
 Extended life of transmissions, gearboxes and final drives
 Outstanding stability to shear stresses
 Maintenance of viscosity throughout the entire service life
 Exceptional thermal stability
 Excellent deposit control
 Compatibility with typical seals in the automotive sector

SPECIFICATIONS

API GL-5
 DAF
 MAN 342 TYPE M1
 ROBERT BOSCH TE-ML 08
 ZF TE-ML 07A / 16D / 21A
 VOLVO 97310

Property	Method	SANEG DRIVELINE GL-5 85W-140
Kinematic Viscosity @40°C, mm ² /s	ASTM D445	372,0
Kinematic Viscosity @ 100°C, mm ² /s	ASTM D445	25,4
Viscosity Index	ASTM D2270	89
Flash Point (COC), °C	ASTM D92	212
Pour Point, °C	ASTM D97	-24
Density @ 15°C, kg/l	ASTM D1298	0,913

Product information is contained in the relevant safety data sheet (SDS). This sheet provides guidance on potential hazards, precautions and first aid measures, together with environmental effects and disposal of used products. SDSs are available upon request from the sales office. This product must not be used for any purpose other than its intended use. Edition 01/2025