

SANEG GREASE CA 2

SANEG Grease CA 2 is high performance multipurpose calcium grease, formulated with highly-refined mineral bases and anhydrous calcium thickener with outstanding water washout properties. It is suitable for most industrial applications, for lubrication of plain and anti-friction bearings in vehicles, as well as in construction and agricultural machinery, when EP characteristics are not required, in the operating temperature range from -20°C to +100°C.

APPLICATIONS

Recommended for marine, agricultural, construction, off-road and industrial applications with moderate loads when resistance to the action of water is required.

PERFORMANCE

Excellent water and corrosion resistance in humid and marine environments
 High adhesion to metal surfaces which guarantees continuity of lubrication
 Mechanical stability that avoids loss of lubrication performance and oil leakage
 Smooth and homogeneous appearance and high resistance to oxidation
 High anti-rust and anti-corrosion protection of components and machinery

SPECIFICATIONS

DIN 51502 K 2 G-20

Properties	Method	Results
Thickener type		Anhydrous Calcium
Colour	visual	Yellow
Worked penetration, 60x, mm/10-1	ASTM D217	265-295
Dropping point, °C	ASTM D566	>160
Base oil viscosity@40°C, mm ² /s	ASTM D445	100
Rust protection, distilled water	ASTM D6138	pass
Water Washout, 79°C, %	ASTM D 1264	3

Product information is contained in the relevant safety data sheet (SDS). This sheet provides guidance on potential hazards, precautions and first aid measures, together with environmental effects and disposal of used products. SDSs are available upon request from the sales office. This product must not be used for any purpose other than its intended use. Edition 01/2025