

SANEG GREASE L 2/100

SANEG Grease L 2/100 is a multifunctional NLGI 2 lithium grease for bearing and component lubrication, electric motors and high-speed applications. It is suitable for most industrial applications, for the lubrication of plain and anti-friction bearings in vehicles, as well as in construction and agricultural machinery, when EP characteristics are not required, in the operating temperature range from -30°C at +120°C.

APPLICATIONS

Recommended for general industrial lubrication, anti-friction bearings, lightly loaded plain bearings, electric motors, machine tools and centralized lubrication systems

PERFORMANCE

It guarantees excellent lubrication performance up to +120°C
It has a smooth and homogeneous appearance and high resistance to oxidation
It ensures high anti-rust and anti-corrosion protection of components and machinery
It extends bearing life in humid environments by reducing maintenance costs and downtime

SPECIFICATIONS

DIN 51502 K 2 K-30

Properties	Method	Results
Thickener type		Lithium
Colour	visual	Brown
Worked penetration,, 60x, mm/10-1	ASTM D217	265-295
Dropping point, °C	ASTM D566	>190
Base oil viscosity@40°C, mm ² /s	ASTM D445	100
Rust protection, distilled water	ASTM D6138	pass
Copper corrosion, 24 hours @ 120°C	DIN 51811	1B

Product information is contained in the relevant safety data sheet (SDS). This sheet provides guidance on potential hazards, precautions and first aid measures, together with environmental effects and disposal of used products. SDSs are available upon request from the sales office. This product must not be used for any purpose other than its intended use. Edition 04/2025