

SANEG GREASE LF 2

SANEG Grease LF 2 is a multifunctional NLGI 2 lithium stringy grease for industrial and agricultural applications. Green in colour, it contains a specific additive to allow strong adhesiveness and maximum extensibility of the filament, ensuring correct lubrication of the parts operating in conditions of strong stress and shock loads. Characterized by excellent mechanical stability, excellent resistance to oxidation and ageing, it has great resistance to water washout. It is recommended for use in the operating temperature range from -30°C to +120°C.

APPLICATIONS

Recommended for agricultural and industrial applications, for grease lubrication points of various machinery (cranes, excavators, tractors, cotton openers) and for mechanical parts operating under conditions of high loads, vibrations, shocks, when EP properties are not necessary.

PERFORMANCE

It guarantees continuity of lubrication even in difficult conditions thanks to the high adhesiveness and extensibility of the filament, remaining attached in the presence of heavy loads or shocks and vibrations for good reliability and availability of the equipment.

Resists water washout, corrosion and softening to prevent lubrication failures and oil spills, extending bearing life in humid environments

SPECIFICATIONS

DIN 51502 K 2 K-30

Properties	Method	Results
Thickener Type		Lithium
Colour	visual	Green
Penetration, worked 60 stokes, mm/10-1	ASTM D217	265-295
Dropping Point, °C	ASTM D566	>190
Base Oil Viscosity @40°C, mm ² /s	ASTM D445	100
Rust Protection, distilled water	ASTM D6138	pass
Water washout, 79°C, %	ASTM D1264	3

Product information is contained in the relevant safety data sheet (SDS). This sheet provides guidance on potential hazards, precautions and first aid measures, together with environmental effects and disposal of used products. SDSs are available upon request from the sales office. This product must not be used for any purpose other than its intended use. Edition 04/2025