

## SANEG GREASE L 00

SANEG Grease L 00 is a multifunctional NLGI 00 lithium grease for the lubrication of bearings and mechanical components under normal load conditions. It ensures excellent pumpability and protection from rust and corrosion. It is recommended for use in the operating temperature range of -30°C to +120°C.

### APPLICATIONS

Recommended for moderate bearing conditions found in centrally lubricated equipment and for some lightly loaded gearbox applications. Excellent performance in low temperature applications.

### PERFORMANCE

Excellent pumpability at low temperatures  
Stability under vibrations and no leakages due to grease softening  
Excellent rust and corrosion resistance.

### SPECIFICATIONS

DIN 51502 K 00 K-30

| Properties                                   | Method     | Result  |
|--|------------|---------|
| Thickener type                               |            | Lithium |
| Colour                                       | visual     | Brown   |
| Worked penetration, 60x, mm/10-1             | ASTM D217  | 400-430 |
| Dropping point, °C                           | ASTM D566  | >190    |
| Base oil viscosity @40°C, mm <sup>2</sup> /s | ASTM D445  | 150     |
| Rust Protection, distilled water             | ASTM D6138 | pass    |

Product information is contained in the relevant safety data sheet (SDS). This sheet provides guidance on potential hazards, precautions and first aid measures, together with environmental effects and disposal of used products. SDSs are available upon request from the sales office. This product must not be used for any purpose other than its intended use. Edition 04/2025