

SANEG GREASE L 1

SANEG Grease L 1 is a multifunctional NLGI 1 lithium grease for the lubrication of bearings and mechanical components under normal load conditions. It ensures excellent pumpability and protection from rust and corrosion. It is recommended for use in the operating temperature range of -30°C to +120°C.

APPLICATIONS

Recommended for moderate bearing conditions found in centrally lubricated equipment and for some lightly loaded gearbox applications. Excellent performance in low temperature applications.

PERFORMANCE

Recommended for moderate bearing conditions found in centrally lubricated equipment and for some lightly loaded gearbox applications. Excellent performance in low temperature applications.

SPECIFICATIONS

DIN 51502 K 1 K-30

Properties	Method	Result
Thickener type		Lithium
Colour	visual	Brown
Worked penetration, 60x, mm/10-1	ASTM D217	310-340
Dropping point, °C	ASTM D566	>190
Base oil viscosity @40°C, mm ² /s	ASTM D445	150
Rust Protection, distilled water	ASTM D6138	pass

Product information is contained in the relevant safety data sheet (SDS). This sheet provides guidance on potential hazards, precautions and first aid measures, together with environmental effects and disposal of used products. SDSs are available upon request from the sales office. This product must not be used for any purpose other than its intended use. Edition 04/2025