

## SANEG GREASE L 3

SANEG Grease L 3 is a multifunctional NLGI 3 lithium grease for the lubrication of bearings and mechanical components, that require medium-hard consistency. It is suitable for a wide range of applications where maximum protection against the penetration of water or solid contaminants is required. It is recommended for use with normal loads in the operating temperature range from -30°C to +120°C.

### APPLICATIONS

Recommended for general industrial lubrication, wheel bearings of cars and heavy vehicles, electric motors, transmission shafts, agricultural equipment, when EP characteristics are not required.

### PERFORMANCE

Thanks to the excellent performance up to + 120 ° C it guarantees a longer bearing life. It ensures excellent mechanical stability even in case of vibrations and no losses due to grease softening. Extends bearing life in humid environments by reducing maintenance costs and unexpected downtime. Maintains a stable consistency during long storage periods.

### SPECIFICATIONS

DIN 51502 K 3 K-30

Properties	Method	Result
Thickener type		Lithium
Colour	visual	Brown
Worked penetration, 60x, mm/10-1	ASTM D217	220-250
Dropping point, °C	ASTM D566	>190
Base oil viscosity @40°C, mm <sup>2</sup> /s	ASTM D445	150
Rust Protection, distilled water	ASTM D6138	pass

Product information is contained in the relevant safety data sheet (SDS). This sheet provides guidance on potential hazards, precautions and first aid measures, together with environmental effects and disposal of used products. SDSs are available upon request from the sales office. This product must not be used for any purpose other than its intended use. Edition 04/2024