SANEG GREASE L EP 2/220 BLU

SANEG Grease L EP 2/220 Blu is a multipurpose NLGI 2 lithium grease for the lubrication of bearings and components subjected to severe loads and severe operating conditions such as shock loads and water contamination. It is formulated with high viscosity index base oils, lithium hydroxystearate soap and EP additives to guarantee excellent lubrication performance in a wide operating temperature range from -30°C to +120°C. The blue color makes it easily recognizable.

APPLICATIONS

Recommended for general industrial lubrication, rolling bearings and plain bearings, industrial applications, bearings in vehicles, construction and agricultural machinery, where components are subject to high loads and water contamination.

PERFORMANCE

It guarantees excellent lubrication performance even under very severe loads up to +120°C
It offers excellent resistance to water washout, extending the life of bearings in humid environments
It has a blue, smooth and homogeneous appearance and excellent resistance to oxidation
It ensures high anti-rust and anti-corrosion protection of components and machinery
Reduces maintenance costs and downtime

SPECIFICATIONS

DIN 51502 KP 2 K-30

Properties	Method	Results
Thickener type		Lithium
Colour	visual	Blue
Worked penetration, 60x, mm/10-1	ASTM D217	265-295
Dropping point, °C	ASTM D566	>190
Base oil viscosity@40°C, mm^2/s	ASTM D445	220
4-Ball Weld Load, kgf	ASTM D2596	315
Rust Protection, distilled water	ASTM D6138	supera
Water Washout, 79°C, %	ASTM D1264	<4

Product information is contained in the relevant safety data sheet (SDS). This sheet provides guidance on potential hazards, precautions and first aid measures, together with environmental effects and disposal of used products. SDSs are available upon request from the sales office. This product must not be used for any purpose other than its intended use. Edition 03/2025

SANEG OIL ITALY SPA
Via Francesco Benaglia 13
00153 Rome – Italy
Tel.: +39 06 83971600

While the information and data provided here is typical of current production and within specifications, minor variations may occur. If you need further information, consult our technical helpdesk.
E-mail: techinfo@saneg-oil.it