REYNCHEMIE NV/SA
Industrieweg 25
Tel. +32-51-24.25.27
B-8800 ROESELARE (Belgium)
reynchemie@reynchemie.com

Uw partner in restauratie en renovatie
Votre partenaire en restauration et rénovation
Your partner in restauration and renovation

RC CONCRETE CLEAN+

CONCENTRATED MAINTENANCE CLEANER, SPECIALLY FORMULATED TO CLEAN POLISHED CONCRETE

Concrete post-treatment, hardening and curing | Cleaning products



ADVANTAGES OF RC CONCRETE CLEAN+

- ✓ Maintains hardness and shine
- ✓ Flexible dilution for both surface and deep cleaning
- ✓ Rinsing is not required for routine cleaning
- ✓ Reduces the visibility of minor scratches
- ✓ Ideal for scrubber-dryers

Description

RC CONCRETE CLEAN+ is a maintenance cleaner, specially designed for treated concrete floors and untreated concrete floors.

RC CONCRETE CLEAN+ contains a lithium silicate hardener that provides an additional protective layer to the concrete floor during cleaning. RC CONCRETE CLEAN+ is specially designed for floors treated with RC M040, RC M050-LIT and RC M060+, but can also be used on untreated concrete floors.

A weekly maintenance cleaning with RC CONCRETE CLEAN+ improves the qualities and properties as well as the service life of the treated floors.

Properties

- Maintains the hardness and shine of concrete floors;
- Removes most common soiling;
- Flexible dilution for both surface and deep cleaning;
- Removes persistent oil stains;
- Easily biodegradable;
- Reduces the visibility of minor scratches;
- Concentrated for economical storage and transportation;
- Rinsing is not required for routine surface cleaning of floors;
- Ideal for scrubber-dryers.

Limitation

- Some embedded stains may not be removed.

Application instructions

To clean deeply embedded oil and grease stains, treat with RC 14 (see technical data sheet).

1. Remove dust and dirt from the concrete floor to be cleaned;
2. Apply with a mop or an automatic scrubber-dryer;
3. After application, there is no need to rinse the floor;
4. Do not allow puddles or concentrated cleaner to dry on the floor;
5. Buffing the cleaned floor with a white pad enhances the gloss.

Consumption

Dilution

- Normal weekly maintenance: 8–10 ml per litre of water
- Deep cleaning (heavy soiling): 32–40 ml per litre of water

Coverage (per litre of ready-to-use solution)

- Automatic scrubber-dryer: approx. 12 m^2/L
- Mop and bucket: approx. 6–7 m^2/L

Converted per litre of RC CONCRETE CLEAN+:

- Normal maintenance: approx. 1,200–1,500 m^2 with a scrubber-dryer or approx. 600–850 m^2 with mop and bucket
- Deep cleaning: approx. 300–375 m^2 with a scrubber-dryer or approx. 150–220 m^2 with mop and bucket

Actual consumption depends on the degree of soiling, the porosity of the floor and the equipment used.

Technical characteristics

Appearance	Light greenish liquid with fresh odor
pH-value	11 - 12
Density	1,02 kg/L
Flash point	Not applicable
VOC-content	< 1 %

Safety

Consult the most recent safety data sheet.

Cleaning of equipment

With water immediately after use.

Storage / Shelf life

12 months from production in the original, sealed packaging. Store in a cool, well-ventilated, frost-free place;

protect from moisture.

Packaging

5 liters (art.no. 110134)

10 liters (art.no. 110135)

Photos







Legal Notes

The information and recommendations contained in this document have been prepared in good faith based on the current knowledge and experience of Reynchemie, concerning products that are correctly stored, handled and applied under normal conditions and in accordance with our guidelines. Since practical conditions, materials and substrates may vary from one application to another, Reynchemie cannot guarantee the merchantability or suitability of the product for a particular purpose. The user remains responsible for carrying out preliminary tests to verify the compatibility of the product with the intended application. All stated values and properties are average results determined at 20 °C; reasonable deviations are acceptable. Products used in combination with this product within the same application system (such as preparation or finishing products) must always be applied according to the instructions provided in their respective technical data sheets. Reynchemie reserves the right to modify the composition or properties of its products without prior notice. Except where mandatory legal provisions apply, Reynchemie accepts no liability for damage resulting from improper application of its products or from failure to comply with the provided instructions. Third-party property rights must always be respected. All orders are accepted under the applicable sales and delivery conditions. Users must always consult the latest version of the local Technical Data Sheet (TDS) and Safety Data Sheet (SDS) for the respective product; copies will be provided upon request if not available on our website www.reynchemie.com. This document supersedes all previous versions.