



ASB is a spiral-cut thermoplastic tubing designed for cable management. This spiral bind product organises and neatens cables and wires, making it ideal for both office and home environments.

## DIMENSIONS

Product	Supplied ID (mm)	Range (mm)	Wall Thickness (mm)	Roll Qty (m)
ASB3.2	3.2	3 - 6	0.6	30
ASB6.4	6.4	6 - 12	1	30
ASB12.7	12.7	12 - 20	1.2	30
ASB20	20	20 - 30	1.2	30

Custom colours available on request



## KEY FEATURES

- Operating temperature -25 °C to 70 °C
- Different wall thicknesses are available on request
- Colours: Black and Natural, others on request
- Easy to use

## APPLICATION

- Cable management of telecoms and data cables at the office and home.
- Cable harnesses, keeping individual wires together during assembly.
- Mechanical protection and colour coding for hydraulic and pneumatic hoses.

## TECHNICAL DATA

Properties	Test Methods	Typical Values
Tensile (MPa)	IEC 60811	> 14
Elongation (%)	IEC 60811	> 250
Heat ageing: Tensile (MPa) : Elongation (%)	IEC 60811 (100 °C x 168 hrs)	>12 > 250
Heat shock (150°C x 1hr)	IEC 60811	No cracking
Cold elongation -25°C	ASTM D 2671	No cracking
Hot deformation (95°C x 1hr) %	IEC 60811	< 50
Dielectric strength (kV/mm)	ASTM D 2671	> 20
Volume resistivity (Ω/cm)	ASTM D 257	10 <sup>14</sup>
Designed for UV stability (on request)		10 years

## STANDARD COLOURS

