



This specially formulated polyvinyl chloride tubing features a thin wall, making it ideal for use in harness and electronic assembly applications requiring reliable performance.

DIMENSIONS

Product	ID (mm)	Nom. Wall Thickness (mm)
PVC1	1	0.4
PVC2	2	0.4
PVC3	3	0.4
PVC4	4	0.4
PVC5	5	0.4
PVC6	6	0.5
PVC7	7	0.5
PVC8	8	0.5
PVC9	9	0.5
PVC10	10	0.5
PVC11	11	0.5
PVC12	12	0.6
PVC14	14	0.6
PVC16	16	0.7
PVC18	18	0.7
PVC19	19	0.7
PVC20	20	0.8
PVC22	22	0.9
PVC25	25	0.9
PVC28	28	0.9
PVC30	30	0.9
PVC35	35	0.9

KEY FEATURES

- *Very flexible*
- *Thin wall thickness*
- *Colours: Black and white, other colours on request*
- *Custom length cutting available upon request*
- *Complies with SANS 1411 - Type S2 and D3 Test method SANS 60811*

APPLICATION

- All harnesses including automotive, slot machines, mining equipment, industrial equipment.
- Colour coding of cables.

TECHNICAL DATA

Properties	Typical Values
Material	PVC (Polyvinylchloride)
Operating temperature (°C)	-15 to 70
Heatshock (°C)	150
Volume resistivity at 20 °C Min (Ω/cm)	2 x 10 ¹¹

STANDARD COLOURS

