



## TI

## Semi-Rigid Terminal Insulation

### Product Description

Grayline TI is a heat shrinkable polyolefin that is specially sized for terminal insulation. This semi-rigid polyolefin is designed to provide strain relief for terminals, spades, and lugs

*Standard Packaging: Cut Pieces*  
*Standard Color: Black,*

### Specifications

- SAE-AMS-DTL-23053/6
- EU Directive 2000/53/EC (ELV)
- EU Directive 2011/65/EU (RoHS2)
- EU Directive 2015/863 (RoHS3)

### Features

- 2.5:1 Shrink Ratio
- Operating Temperature is  $-55^{\circ}\text{C}$  to  $135^{\circ}\text{C}$
- Shrinks at  $135^{\circ}\text{C}$
- Strain Relief
- Specially Sized
- Supplied in 1" Cut Pieces

### Standard Sizes

NOMINAL SIZE	EXPANDED INSIDE DIAMETER (MINIMUM)	RECOVERED INSIDE DIAMETER (MAXIMUM)	RECOVERED WALL THICKNESS
1	.240"	.095"	.032"
2	.320"	.125"	.032"
3	.375"	.150"	.032"
4	.485"	.200"	.032"

*The values listed in this bulletin, to the best of our knowledge, are accurate. They are typical performance results and are not intended to be used as design data. We disclaim all liability in connection with the use of information contained herein or otherwise.*