



MWT

Medium Wall Adhesive-Lined Polyolefin

Product Description

Grayline MWT is a medium wall 3:1 adhesive lined heat shrinkable polyolefin. MWT is suitable for low voltage electrical and mechanical applications. The inner adhesive wall melts and fills small voids to provide a complete environmental seal against water and dirt.

Standard Packaging: 4' Lengths (Cut-Lengths Available Upon Request)

Standard Color: Black, Red, Clear

Specifications

- EU Directive 2000/53/EC (ELV)
- EU Directive 2011/65/EU (RoHS2)
- EU Directive 2015/863 (RoHS3)

Features

- 3:1 Shrink Ratio
- Operating Temperature is -55°C to 110°C
- Shrinks at 120°C
- Flexible
- Creates an Environmental Seal
- Accepts Surface Markings
- Lead-Free

Standard Sizes

NOMINAL SIZE	EXPANDED INSIDE DIAMETER (MINIMUM)	RECOVERED INSIDE DIAMETER (MAXIMUM)	RECOVERED WALL THICKNESS
0400	0.400	0.150	0.080
0750	0.750	0.220	0.080
1100	1.100	0.400	0.095
1300	1.300	0.400	0.095
1500	1.500	0.500	0.095
1700	1.700	0.500	0.100
2050	2.050	0.750	0.100
2750	2.750	1.000	0.100
3500	3.500	1.180	0.100
4700	4.700	1.570	0.105
6000	6.000	2.000	0.120
6700	6.700	2.300	0.120
9000	9.000	3.000	0.130

The values listed in this bulletin, to the best of our knowledge, are accurate. They are typical performance results and are not intended to be used as design data. We disclaim all liability in connection with the use of information contained herein or otherwise.