



Contact your local dealer or
Lindsay Windows
for more information.

North Mankato, Minnesota
(507) 625-4278

Union, Missouri
(636) 583-0850

Aurora, Illinois
(630) 892-5091

Other Manufacturing Facilities
Georgia, Washington, California

Thank you for considering
DuraPro Windows 300.



A TRADITION OF QUALITY SINCE 1947

Lindsay Windows began over 72 years ago as a privately held, family-owned company, which it still is today. Our mission has always been to manufacture the highest quality products using materials with advanced manufacturing equipment and procedures.

Our products carry extensive industry certifications and are distributed through a network of qualified dealers. All of our products exceed the current standards for ENERGY STAR compliance and have some of the best ratings in the industry.

Our modern production facilities in Minnesota, Missouri, Illinois, Georgia, Washington and California manufacture vinyl products for energy specific geographical window and door markets. We value our employees and consider every employee a salesperson for our company. It is a privilege to provide you with the finest products that are the best value in the market, with the best energy performance and warranty. Our best testimonies come from our thousands of satisfied customers. We want you to be one of them.

Our prices reflect our commitment to craftsmanship, advanced materials and superior performance. We are proudly the third owners of Lindsay Windows for the last 30 years.

Thank You,

Authorized Dealer



New Construction
& Remodel
Vinyl Window System



www.LindsayWindows.com

Single Hung Features & Benefits



- ▶ Fusion welded frame and sash corners assures strength, durability, and years of trouble-free service in the home.
- ▶ Cam Locks with keepers fastened into reinforcements provide greater security and reduced air infiltration.
- ▶ 3/4" Extruded J-channel; 2 1/7" jamb
- ▶ Dual locks on widths 24" and above.
- ▶ 1/4" insulated glass available with soft coat Low-E glass.
- ▶ Integral J-channel eliminates the need for J-channel in most siding applications.
- ▶ Optional J-channel filler can be used for cement siding and other siding applications.
- ▶ Reinforcement in fixed meeting rail is continuous for structural integrity.
- ▶ Positive interlock provides increased security and reduces air infiltration.
- ▶ Tilt-in lower sash for easy cleaning.
- ▶ Strong sill provides elegant look from the outside and decreases the possibility of a bowed sill.
- ▶ Bulb seal at bottom of lower sash provides a tight fit between the sash and frame.
- ▶ Inverted block and tackle balances provide smooth operation.
- ▶ Traditional (WM180) brick mould exterior provides an attractive look on the exterior of the window.
- ▶ Standard 3-0 x 5-0 (35 1/2" x 59 1/2" make size) meets 5.7 square feet of opening (egress for most areas).
- ▶ Extruded sash lift rail for easy operation.
- ▶ 1 1/4" extruded nail-fin with pre-punched holes for installation.
- ▶ Standard choice of Painters white, sandstone or clay color




J-Channel & Integral Nailing Fin

The 1-1/4" Integral, pre-punched nailing fin is designed for easy and accurate siding installation. The 3/4" Integral J-channel conceals siding and may eliminate the need for applied J-channel.



Tilt-In Window

Your 301 single hung window utilizes special hardware for easy cleaning. The operable sash tilts-in to enable cleaning your glass from inside your home.




Glass Options/Low-E, Argon

LowE is a microscopically thin, virtually invisible coating deposited on a glass surface. This coating limits radiant heat flow between window panes by reflecting heat away from your home during the warm weather and keeps heat in your home during cold weather.


COLOR CHOICES



WHITE



CLAY



SANDSTONE

*Actual colors may vary from swatches

EXTERIOR LAMINATES



BLACK



BRONZE

GRID



STANDARD FLAT

331 Slider Window

- ▶ Fusion welded frame and sash corners assures
- ▶ Easy lift out operable sash
- ▶ Brass adjustable rollers for easy operation
- ▶ 2 1/4" Jamb and 1 9/16" from nailing fin
- ▶ 3 Lite slider available as XOX in a 1/3 1/3 1/3 or 1/4 1/2 1/4 configuration
- ▶ Reinforcement in fixed meeting rails
- ▶ Locks and keepers are secured into extruded aluminum reinforcement.
- ▶ Dual locks on sliders over 24" in height
- ▶ 1 1/4" Extruded nail-fin with pre-punched holes for installation.



340 Picture Window & Shapes

- ▶ Interior glaze system
- ▶ Variety of shapes are available including half rounds, eyebrows, trapezoids, hexagons, etc.



888 Patio Door

- ▶ Extruded nail-fin for installation with overall jamb of 4 1/2" (3 1/4" inside fin)
- ▶ Welded frame and sash
- ▶ Zinc plated ball bearing rollers provide quiet and smooth operation
- ▶ Handle color to match the frame
- ▶ 3/4" Tempered Insulated glass
- ▶ Heavy duty sliding screen