



SheerWeave 2360

SOLAR FABRIC (10%)

AVAILABLE COLOURS

Brite White P84	
Oyster P12	
Oyster/Beige P13	
Oyster/Pearl Gray P14	
Beige Q20	
Beige/Pearl Gray Q21	
Pearl Gray V20	
Charcoal V21	
Charcoal/Gray V22	
Charcoal/Chestnut V24	
Charcoal/Alpaca V32	

FABRIC SPECIFICATIONS

Stock Widths:	63" / 98" / 126"
Openness:	10 %
Composition:	35% Fiberglass 65% Vinyl on Fiberglass
Thickness:	.019"
Weight:	10.40 oz/yd²
Fire Rating:	NFPA 701 / CA US Title 19 CAN/ULC-S109
Cleaning Info:	Contact Manufacturer
Spline:	SnapLoc
Railroading:	Not Recommended
Acoustical Value:	NRC .05 / SAA .06
Bacterial/Fungal Resistance:	ASTM E2180, D3273, G21, G22 & GreenGuard ASTM 6329



A full basketweave designed expressly for applications which require a more opaque and nondirectional fabric. Can also be used for exterior roller shades.

If you require additional fabric samples please E-mail: samples@frasershading.com

Actual fabric colours may vary from pictures | Fabric stock levels may vary

Openness factors are approximate | Mockups are recommended

Specification subject to change without notice | ©Fraser Shading Systems 2024



FRASER SHADING SYSTEMS | Unit 101 – 5219 192nd Street | Surrey, BC, Canada V3S 4P6

Off: 604-881-4881 | Fax: 604-881-4882 | www.frasershading.com | www.instagram.com/fraser_shading_systems

SheerWeave 2360

(10% openness)

CODE	COLOR	SOLAR OPTICAL PROPERTIES				SHGC/G VALUE	
		TS	RS	AS	TV	g-tot (glass & blind)	
						SINGLE 1/4 CL	INSULATING 1 HA
P84	Brite White	29	61	10	27	0.34	0.24
P12	Oyster	28	62	10	27	0.34	0.24
P13	Oyster/Beige	26	58	16	24	0.36	0.25
P14	Oyster/Pearl Gray	23	48	29	21	0.41	0.27
Q20	Beige	25	48	27	22	0.41	0.27
Q21	Beige/Pearl Gray	21	42	37	18	0.43	0.29
V20	Pearl Gray	19	32	49	17	0.48	0.31
V21	Charcoal	12	4	84	12	0.62	0.38
V22	Charcoal/Gray	12	8	80	12	0.60	0.37
V24	Charcoal/Chestnut	11	6	83	11	0.61	0.37
V32	Charcoal/Alpaca	13	14	73	12	0.57	0.35

TS = Solar Transmittance
 RS = Solar Reflectance
 AS = Solar Absorptance
 TV = Visual Transmittance

SHGC = Solar Heat Gain Coefficient

1/4 CL = 1/4" Clear Glass
 1 HA = 1" Heat Absorbing Glass

Fabrics Installed Internally
 Zero-Degree Profile Angle



CERTIFICATE OF COMPLIANCE



Phifer Incorporated

SheerWeave® Style 2360

Average Openness: 10%

3002-420

Certificate Number

27/Jun/2007 - 20/Jul/2025

Certificate Period

Certified

Status

UL 2818 - 2022 Gold Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Window treatments are determined compliant in accordance with California Department of Public Health (CDPH) Standard Method V1.2-2017 using an Office and Classroom Environment. Product tested in accordance with UL 2821 test method to show compliance to emission limits on UL 2818. Section 7.1 and 7.2.

GREENGUARD Gold Certification Criteria for Building Products and Interior Finishes

Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC (A)	-	0.22	mg/m ³
Formaldehyde	50-00-0	9 (7.3 ppb)	µg/m ³
Total Aldehydes (B)	-	0.043	ppm
4-Phenylcyclohexene	4994-16-5	6.5	µg/m ³
Particle Matter less than 10 µm (C)	-	20	µg/m ³
1-Methyl-2-pyrrolidinone (D)	872-50-4	160	µg/m ³
Individual VOCs (E)	-	1/2 CREL or 1/100th TLV	-

- (A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate. Maximum allowable predicted TVOC concentrations for GREENGUARD Gold (0.22 mg/m³) fall in the range of 0.5 mg/m³ or less, as specified in CDPH Standard Method v1.2.
- (B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.
- (C) Particle emission requirement only applicable to HVAC Duct Products with exposed surface area in air streams (a forced air test with specific test method) and for wood finishing (sanding) systems.
- (D) Based on the CA Prop 65 Maximum Allowable Dose Level for inhalation of 3,200 µg/day and an inhalation rate of 20 m³/day
- (E) Allowable levels for chemicals not listed are derived from the lower of 1/2 the California Office of Environmental Health Hazard Assessment (OEHHA) Chronic Reference Exposure Level (CREL) as required per the CDPH/EHLB/Standard Method v1.2 and BIFMA level credit 7.6.2 and 1/100th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



FRASER SHADING SYSTEMS | Unit 101 – 5219 192nd Street | Surrey, BC, Canada V3S 4P6

Off: 604-881-4881 | Fax: 604-881-4882 | www.frasershading.com | www.instagram.com/fraser_shading_systems