



# Classic 0700

## MECHO BLACKOUT FABRIC (0%)

<u>COLOUR CODE</u>	<u>FRONT</u>	<u>BACK</u>	<u>FABRIC SPECIFICATIONS</u>	
White 0701			Stock Width:	<b>72"</b>
Light Grey 0702			Openness:	<b>0 %</b>
Champagne 0705			Composition:	<b>73% Vinyl Coating 27% Fiberglass</b>
Oyster 0706			Thickness:	<b>.013"</b>
Dark Grey 0711			Weight:	<b>12.50 oz / yd<sup>2</sup></b>
Graphite 0717			Fire Rating:	<b>NFPA 701 / CA US Title 19 CAN/ULC-S109</b>
Black / White 0731			Cleaning Info:	<b>Contact Manufacturer</b>
			Bacterial & Fungal Resistance:	<b>ASTM G21 / ASTM E2180</b>
			Spline:	<b>SnapLoc</b>
			Railroading:	<b>Yes</b>



This opaque vinyl material is ideal where complete darkness is required. It is flame retardant, fade resistant, and provides insulation. The window facing side of this shade cloth is the same color as the interior color.

For 0731 - Black/White, the window facing side is white.

If you require fabric samples please E-mail: [samples@frasershading.com](mailto:samples@frasershading.com) | Actual fabric colours may vary from pictures

Fabric stock levels may vary | Openness factors are approximate | Mockups are recommended

Specification subject to change without notice | ©Fraser Shading Systems 2025



# CERTIFICATE OF COMPLIANCE



## Mecho

### Classic Blackout 0700 Series (opaque)

19375-420

Certificate Number

02 Jun 2011 - 02 Jun 2026

Certificate Period

Certified

Status

UL 2818 - 2022 Gold Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Window treatments are determined compliant in accordance with California Department of Public Health (CDPH) Standard Method V1.2-2017 using an Office and Classroom Environment. Product tested in accordance with UL 2821 test method to show compliance to emission limits on UL 2818. Section 7.1 and 7.2.

### GREENGUARD Gold Certification Criteria for Building Products and Interior Finishes

Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC (A)	-	0.22	mg/m <sup>3</sup>
Formaldehyde	50-00-0	9 (7.3 ppb)	µg/m <sup>3</sup>
Total Aldehydes (B)	-	0.043	ppm
4-Phenylcyclohexene	4994-16-5	6.5	µg/m <sup>3</sup>
Particle Matter less than 10 µm (C)	-	20	µg/m <sup>3</sup>
1-Methyl-2-pyrrolidinone (D)	872-50-4	160	µg/m <sup>3</sup>
Individual VOCs (E)	-	1/2 CREL or 1/100th TLV	-

- (A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate. Maximum allowable predicted TVOC concentrations for GREENGUARD Gold (0.22 mg/m<sup>3</sup>) fall in the range of 0.5 mg/m<sup>3</sup> or less, as specified in CDPH Standard Method v1.2.
- (B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.
- (C) Particle emission requirement only applicable to HVAC Duct Products with exposed surface area in air streams (a forced air test with specific test method) and for wood finishing (sanding) systems.
- (D) Based on the CA Prop 65 Maximum Allowable Dose Level for inhalation of 3,200 µg/day and an inhalation rate of 20 m<sup>3</sup>/day
- (E) Allowable levels for chemicals not listed are derived from the lower of 1/2 the California Office of Environmental Health Hazard Assessment (OEHHA) Chronic Reference Exposure Level (CREL) as required per the CDPH/EHLB/Standard Method v1.2 and BIFMA level credit 7.6.2 and 1/100th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



FRASER SHADING SYSTEMS | Unit 101 – 5219 192<sup>nd</sup> Street | Surrey, BC, Canada V3S 4P6

Off: 604-881-4881 | Fax: 604-881-4882 | [www.fraser shading.com](http://www.fraser shading.com) | [www.instagram.com/fraser\\_shading\\_systems](https://www.instagram.com/fraser_shading_systems)