




androidtv



TG STREAM ANDROID TV 4K BOX with DVB-T

TG STREAM - 4K Ultra HD Android TV STB is a Google authorized, and Netflix certified turnkey OTT solution for operators with DVB-T. It is a hybrid box that allows users to enjoy both linear TV and streaming apps.

Upgrade traditional set-top boxes and turn any TV or monitor into a smart Android TV – just plug it in to the TV or monitor's HDMI port. Powered by Android 14 OS and Amlogic S905X5-M chipset, consumers can now access enhanced content through this smart device.



ATV Bridge is a cloud-based service management tool that helps the operators to configure and manage all devices from a single pane of glass. Remote management helps to streamline customer support, thereby reducing truck rolls.



KEY FEATURES

- Operator tier box with option to skip Google sign-in
- Intuitive Remote Screen option to initiate screen sharing session for reducing truck rolls
- Update apps from the ATV Bridge backend
- Customized launcher with options to add logo, scrolling banners, add railings, change themes and more
- Improved RCU with backlit buttons
- Dedicated shortcut button for quick launch of the app
- Ability to auto-launch the app on every boot



HDMI



Ethernet



USB 3.0



S/PDIF



DVB-T/T2



AV Output



www.transliteglobal.com



sales@transliteglobal.com



+1 (713) 979 4401

- Device Certification
- Device Detection
- Grouping

TMS Terminal Management System




ATV Bridge Platform

IoT
Internet of
Things Service



BDC
Big Data
Center




- Device Control Service
- Device Report Service
- Remote Diagnostics Basic Service
- Push Message Service

- Device Status
- CPU Utilization & Temperature
- Wi-Fi & Bluetooth Signal Strength
- Logs



Cloud-based Service Management Tool




Combine delivery of Linear
& Streaming content



Optimal Performance in line
with Industry Standards



Stream Content through a
Modern User Interface



Reduce CSR time
spent on support calls



Reduce Truck Rolls with
proactive problem solution

Hardware Platform

CPU Chipset	Amlogic S905X5-M
DMIPS	30K DMIPS
DVB	DVB-T/T2 Tuner built-in
RAM	2GB LPDDR4
Flash	eMMC 16GB

Network

Wi-Fi	802.11 b/g/n/ac 2.4G/5G Wi-Fi 5
Ethernet	100Mbps
Bluetooth	Bluetooth 5.0

DRM

Widevine Level	Supported, Level 1
PlayReady	Supported, SL3000

Video

Video Decoding	AV1 MP-10@L5.1, VP9 Profile-2, H.265 HEVC MP-10@L5.1, AVS2-P2 Profile, H.264 AVC HP@L5.1, H.264 MVC, MPEG-4 ASP@L5, WMV/VC-1 SP/MP/AP, MPEG-2 MP/HL, MPEG-1 MP/HL, RealVideo 8/9/10
Video Resolution	480i/p, 576i/p, 720p, 1080i/p and 4Kx2K
Video Output	HDMI 2.1, HDCP2.2

Audio

Audio Decoding	Supports MP3, AAC, WMA, RM, FLAC, Ogg and programmable with 7.1/5.1 down-mixing
Audio Mode	Mono/Stereo/Left/Right
Dolby Digital Plus	Supported
DTS	Supported (optional)

Interface

LED indicator light, IR Control, HDMI Output, SPDIF, AV Output, Reset Button, USB Port (1*USB 2.0, 1*USB 3.0), DVB-T/T2 Tuner built-in

Power Supply

DC Input	12V / 1A
Power Consumption	Maximum 12W
Lightning Level	4KV

RCU

IR Support	Supported
Protocol	BLE 5.0
Battery Type	2*AAA 1.5V

General

Weight	< 2lbs
Dimension	114 (W)*114 (L) *22 (H) mm
Operating Temperature	0°C - 50°C
Humidity	< 95%



www.transliteglobal.com



sales@transliteglobal.com



+1 (713) 979 4401