BIG BUSES



RK 1426 | RK 1426 Long | RN 1626





Buses built for Safety and Performance

BATANGAS

RANGE	HINO BUS								
MODEL NAME	RK 1426			RK 1426 Long			RN 1626		
MODEL CODE	RK8JMUA			RK8JSUA			RN8JSUA		
CATEGORY				Big Bus					
TYPE (AIR-CONDITIONING)	Regular Non-A/C	Regular A/C	Deluxe A/C	Regular Non-A/C	Regular A/C	Deluxe A/C	Regular Non-A/C	Regular A/C	Deluxe A/C
DRIVE SYSTEM	4 x 2 (6W)								
GROSS VEHICLE WEIGHT (Kg)	14,000 16,000								
TRANSMISSION	6 Forward and 1 Reverse Speed, Direct-drive, Synchromesh 2nd - 6th								
TIRES & RIMS	11R22.5-16PR								
FUEL TANK CAPACITY (L)	250								
SEATING CAPACITY	5	5	45	55 - 62	57 - 62	46 - 50	60 - 62	62	50
DIMENSIONS									
Wheelbase (mm)	5,200			6,000					
Length (mm)	11,000			12,000					
Width (mm)				2,480					
Height (mm)	3,550 3,800			3,550	3,8	3,800		3,800	
ENGINE									
Model	J08E-UB								
Emission Standard	Euro 4								
Max. Engine Speed (rpm)	2,650								
Туре	Diesel, Turbo-charged & Intercooled, 4-Cycle, Vertical, Inline, 6-Cylinder, Overhead Camshaft, Water-cooled								
Combustion System	Direct Injection Type								
Fuel Injection System	Electronic Control Common Rail Type								
Displacement (L)	7.684								
PERFORMANCE	—): :::::::::::::::::::::::::::::::::::								
Max. Output (PS) ISO Net JIS Gross	250 260								
Max. Torque (Nm) ISO Net JIS Gross	739 745								
Max. Speed (kph)	114 118								
SUSPENSION									
Front	Semi-elliptic Leaf Springs with Silencer, Double Acting Shock Absorbers and Stabilizer Air Suspension with Double Acting Shock Absorbers and Stabilizer								
Rear									
BRAKES	-32								
Type & Features	Full Air, Dual-Circuit, "S" Cam Type, Leading and Trailing Shoes for Front and Rear Wheels								

^{*}Photos may vary from the actual unit.



RK 1426 | RK 1426 LONG



RN 1626









