

MENSA PND 600



TECHNICAL DATA

BODY:	ALUMINUM
DIFFUSER:	MICROPRISMATIC / OPAL
CRI:	>80
COLOR TOLERANCE:	3SDCM (MacAdam)
MAINTENANCE OF LUMINOUS FLUX:	L80/B10 $\geq$ 50.000h, Ta 25 C° L90/B10 $\geq$ 50.000h, Ta 25 C°
FAILURE RATE:	C0/B10 $\geq$ 50.000h, Ta 25 C°
PHOTOBIOLOGICAL SAFETY:	RG1
SOURCE OF LIGHT:	SMD LED
LED LIGHT ANGLE:	120°
COLOR TEMPERATURE:	2700K ~ 6500K
DIMMER:	OPTIONAL
DALI FEATURE:	OPTIONAL
SUPPLY VOLTAGE:	220-240 VAC, 50/60 Hz
PROTECTION CLASS:	IP20
APPLICATION TYPE:	PENDANT
OPERATING TEMPERATURE:	-20 ~ +50C°

PRODUCT DETAILS

POWER:	52
LUMEN:	6240
COLOUR TEMP :	4000K
EXTERIOR COATING :	Electrostatic powder paint 9016
On/Off :	✓

TECHNICAL DRAWING

