

OLIVIA KS



TECHNICAL DATA

BODY:	ALUMINUM
DIFFUSER:	TEMPERED GLASS + REFLECTOR
CRI:	>80 / >90
COLOR TOLERANCE:	3SDCM (MacAdam)
MAINTENANCE OF LUMINOUS FLUX:	L80/B10 \geq 50.000h, Ta 25 C° L90/B10 \geq 50.000h, Ta 25 C°
FAILURE RATE:	C0/B10 \geq 50.000h, Ta 25 C°
PHOTOBIOLOGICAL SAFETY:	RG1
SOURCE OF LIGHT:	COB
LED LIGHT ANGLE:	18° / 24° / 36° / 45°
COLOR TEMPERATURE:	2700K ~ 6500K
DIMMER:	OPTIONAL
DALI FEATURE:	OPTIONAL
SUPPLY VOLTAGE:	220-240 VAC, 50/60 Hz
PROTECTION CLASS:	IP20
APPLICATION TYPE:	RAIL ASSEMBLY
OPERATING TEMPERATURE:	-20 ~ +50C°

PRODUCT DETAILS

POWER:	34
LUMEN:	3500
COLOUR TEMP. :	3000K
EXTERIOR COATING :	Any desired coating can be made.

TECHNICAL DRAWING

