

SWAN V01



TECHNICAL DATA

| | |
|-------------------------------|--|
| BODY: | ALUMINUM |
| DIFFUSER: | TEMPERED GLASS + REFLECTOR |
| CRI: | >90 |
| COLOR TOLERANCE: | 3SDCM (MacAdam) |
| MAINTENANCE OF LUMINOUS FLUX: | L80/B10 \geq 50.000h, Ta 25 C° L90/B10 \geq 50.000h, Ta 25 C° |
| FAILURE RATE: | C0/B10 \geq 50.000h, Ta 25 C° |
| PHOTOBIOLOGICAL SAFETY: | RG1 |
| SOURCE OF LIGHT: | COB |
| LED LIGHT ANGLE: | 18°, 24°, 36°, 45° |
| COLOR TEMPERATURE: | 2700K ~ 6500K |
| DIMMER: | OPTIONAL |
| DALI FEATURE: | OPTIONAL |
| SUPPLY VOLTAGE: | 220-240 VAC, 50/60 Hz |
| PROTECTION CLASS: | IP20 |
| APPLICATION TYPE: | RECESSED |
| OPERATING TEMPERATURE: | -20 ~ +50C° |

PRODUCT DETAILS

| | |
|--------------------|------------------------------------|
| POWER: | 32 |
| LUMEN: | 3520 |
| COLOUR TEMP. : | 3000K |
| EXTERIOR COATING : | Electrostatic powder paint 9016 |

TECHNICAL DRAWING

