

SYSTEM SPECIFICATION

Big Capability. Right-Sized for Your Business.



Xerox® MX831
Multifunction Printer



Xerox® MX833
Multifunction Printer



SYSTEM SPECIFICATION

Xerox® MX831 and MX833 Multifunction Printers



PRINT (UP TO:)		
System Specification	Xerox® MX831 Multifunction Printer	Xerox® MX833 Multifunction Printer
Simplex Speed ¹ – Letter/A4 B&W (Up To:)	55/52 pages per minute (ppm)	70/66 pages per minute (ppm)
Duplex Speed ¹ – Letter/A4 B&W (Up To:)	33/32 images per minute (ipm)	42/40 images per minute (ipm)
Monthly Duty Cycle ² (Up To:) Pages Per Month	300,000 Pages	350,000 Pages
Recommended Average Monthly Print Volume (Up To:) Pages Per Month	75,000 Pages	100,000 Pages
Processor Speed/Memory	1.2 GHz Quad Core, 4GB RAM, Standard 128GB Intelligent Storage Drive (ISD), Optional 256GB SSD, 500GB Hard Disk	
Connectivity	Hi-Speed USB 2.0 (Type B rear; Type A rear (dual) & front (general and card reader use)), Gigabit Ethernet, Wireless 802.11a/b/g/n/ac + Apple iBeacon	
Imaging Technology	Laser	
Functions	Print, Copy, Scan, Fax (Optional)	
Configuration*	MX831se: 100-Sheet Multipurpose Feeder, 550-Sheet Tray, Solutions Enabled (eSF), Standard Intelligent Storage Drive MX831tse*: 100-Sheet Multipurpose Feeder, 2 x 550-Sheet Trays, Caster Base, Solutions Enabled (eSF), Standard Intelligent Storage Drive	MX833se: 100-Sheet Multipurpose Feeder, 550-Sheet Tray, Solutions Enabled (eSF), Standard Intelligent Storage Drive MX833tse*: 100-Sheet Multipurpose Feeder, 2 x 550-Sheet Trays, Caster Base, Solutions Enabled (eSF), Standard Intelligent Storage Drive MX833xse*: 100-Sheet Multipurpose Feeder, 550-Sheet Tray, 2,100-Sheet Tray, Caster Base, Solutions Enabled (eSF), Standard Intelligent Storage Drive
Federal Communications Commission (FCC) Compliance	Class A device. Intended for non-residential/non-domestic environments. Use in residential/domestic environments may cause radio interference.	

PRINT AND COPY		
System Specification	Xerox® MX831 Multifunction Printer	Xerox® MX833 Multifunction Printer
Print Resolution	1200 Image Quality (1200x600 dpi), 1200x1200 dpi (max)	
Copy Resolution (Up To:)	300x300 dpi, 600x600 dpi (max)	
First-print-out Time (As Fast As:)	4.5 seconds	4.0 seconds
First-copy-out Time (As Fast As:)	4.5 seconds	4.0 seconds
Page Description Languages	PostScript® 3 Emulation, PCL® 6 Emulation, PCL® 5 Emulation, PCL® m, and PDF	
Print Features	One-touch UI, Print Quality, Normal, Secure, Saved and Sample Set Job Types, Duplex, Orientation, Collation, Print Job ID in Margins, Draft Mode, N-up, Booklet Layout, Watermark, Tray and Toner Status, Rotate Image 180 Degrees, Saved Settings, Earth Smart Settings	

*Not all models are available in all geographies.

SYSTEM SPECIFICATION

Xerox® MX831 and MX833 Multifunction Printers



MOBILE- AND CLOUD-READY		
System Specification	Xerox® MX831 Multifunction Printer	Xerox® MX833 Multifunction Printer
Mobile Printing	Apple AirPrint®, Mopria® Print Service, Chromebook, Wi-Fi Direct®	
Mobile Scanning	Apple AirPrint®, Mopria® Scan Service	
Xerox® Workplace Suite and Xerox® Workplace Cloud	Yes	
Cloud Connectivity	Yes (via the Xerox® Print and Scan Experience App)	

SCAN		
System Specification	Xerox® MX831 Multifunction Printer	Xerox® MX833 Multifunction Printer
Destinations	Email, Front-side USB Drive, File Transfer Protocol (FTP), Network or USB-connected Computer, Windows Network Folder	
File Formats	TIFF, JPEG, PDF, PNG, Optical Character Recognition available through the Xerox® Print and Scan Experience App for Windows (formats include Scan to Searchable PDF, Word (DOCX), Excel (XLSX))	

FAX		
System Specification	Xerox® MX831 Multifunction Printer	Xerox® MX833 Multifunction Printer
Optional**	MH/MR/MMR/JBIG/JPEG Compression, Auto Answer, Auto Redial, Auto Reduction, Broadcast Send, Junk Fax Filter, Fax Address Book, Fax Forward, which includes: Fax, Email, FTP, Network Folder, Called Number	

PRINT DETAILS		
System Specification	Xerox® MX831 Multifunction Printer	Xerox® MX833 Multifunction Printer
First-print-out Time – B&W (As Fast As:)	4.5 seconds	4.0 seconds
Resolution	1200 Image Quality (1200x600 dpi), 1200x1200 dpi (max)	
Page Description Languages	PostScript® 3 Emulation, PCL® 6 Emulation, PCL® 5 Emulation, PCL® m, and PDF	
Unprintable Page Margin	Print: 4.2 mm from each edge; Copy: 3 mm from each edge	
Print from USB	File Formats: Microsoft® Office Formats (Word, Excel, PPT), PDF, Image Formats (JPEG, TIFF, GIF, BMP, PNG, PCX). Options available to configure prints from USB: Paper source, print blank pages, collate, two-sided printing, pages per side orientation, separator sheets, pages per side, pages per side ordering.	
Print Driver Types/Operating Systems	Windows® 11, Windows® 10, Windows® Server 2025, Windows® Server 2022, Windows® Server 2019, Windows® Server 2016, macOS 27, macOS 26, macOS 15, macOS 14, Microsoft Universal Print with Print Support Application. For the latest information about supported Operating Systems, please visit our Drivers & Downloads page and specify your device at www.support.xerox.com .	
Network Protocols	TCP/IP: HTTP/HTTPS, IPP, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, MS Web Services WSD-Print, 802.1x, Simple Network Management Protocol (SNMP), ThinPrint, Microsoft Universal Print, Bonjour	
Font Capability	PCL® 6: 96 Scalable Fonts; PostScript® Emulation: 163 Scalable Fonts	

**2 Port Fax Card required

SYSTEM SPECIFICATION

Xerox® MX831 and MX833 Multifunction Printers



COPY DETAILS

System Specification	Xerox® MX831 Multifunction Printer	Xerox® MX833 Multifunction Printer
First-copy-out Time – B&W (As Fast As:)	4.5 seconds	4.0 seconds
Simplex Speed (Up To:)	55/52 ppm Letter/A4	70/66 ppm Letter/A4
Duplex Speed (Up To:)	33/32 ppm Letter/A4	42/40 ppm Letter/A4
Sides (Input/Output)	1:1, 1:2, 2:1, 2:2	
Quantity	1-9,999	
Concurrency	Yes (Copy while printing)	
Copy Features	Copy From Size; Copy To Size; Scale 25% to 400%; Darkness/Lightness; Sides 1:1, 1:2, 2:1, 2:2; Duplex; Collate; Content Type (Text, Text/Photo, Photo, Graphics). Create Shortcut; Color; Paper Setup; Advanced Imaging, Auto Center, Background Removal, Contrast, Scan Edge to Edge, Saturation, Color Balance, Edge Erase; Header/Footer; Margin Shift; Overlay; Pages Per Side (2 Pages Per Side, 4 Pages Per Side); Separator Sheets (Between Pages, Between Copies, Between Jobs); Separator Sheet Source	

FAX DETAILS

System Specification	Xerox® MX831 Multifunction Printer	Xerox® MX833 Multifunction Printer
Fax Speed	33.6 kbps	
Memory	Fax storage on the standard 128GB Intelligent Storage Drive (ISD): approx. 127GB (ISD capacity less 1GB)	
Resolution (dpi)	B&W standard: 200×100 send, 200×100, 204×98 receive; B&W fine: 200×200 send, 200×200, 204×196 receive; B&W superfine: 300×300 send, 300×300, 204×391 receive; B&W ultrafine: 600×600 send, 600×600, 400×400, 408×391 receive; Color fine: 200×200 send, 200×200 receive; Color superfine: 300×300 send, 300×300, 400×400 receive	
Fax Features	Auto Answer, Auto Redial, Auto Reduction, Broadcast Send, Junk Fax Filter, Fax Address Book	
Fax Forward Destinations	Fax, Email, FTP, Network Folder, Called Number	

SYSTEM SPECIFICATION

Xerox® MX831 and MX833 Multifunction Printers



SCAN DETAILS		
System Specification	Xerox® MX831 Multifunction Printer	Xerox® MX833 Multifunction Printer
Technology	Flatbed Scanner with Single-pass DADF, Contact Image Sensor (CIS) in ADF and Charge Coupled Device (CCD) in flatbed, Multifeed Detection	
Capability	Single-pass DADF, up to 200 sheets of 20 lb bond/75 gsm	
Concurrency	Yes (Scan while printing)	
Input Speed – B&W/Color (Up To:)	80/76 ipm Simplex Letter/A4, 160/152 ipm Duplex Letter/A4	
Resolution (Up To:)	600x600 dpi	
Resolution (dpi)	75x75, 150x150, 200x200, 300x300, 400x400, 600x600	
Maximum Scan Area - Automatic Document Feeder (ADF)	8.5x25 in	
Maximum Scan Area (ADF)	216x635 mm	
Maximum Scan Area (Platen)	8.5x14 in	
Maximum Scan Area (Platen)	216x356 mm	
Media Weight (ADF)	52–120 gsm	
Network Filing Protocol	FTP, Secure File Transfer Protocol (SFTP), Server Message Block (SMB), USB, Windows Network Folder	
File Formats	Scan Formats: PDF (Searchable PDF available via the Xerox® Print and Scan Experience App), TIFF, JPEG, PNG, Optical Character Recognition (formats include Scan to Searchable PDF, Word (DOCX), Excel (XLSX))	
Scan Driver Compatibility	TWAIN, WIA, ICA	
Scan File Compression Options	PDF: 1 bit – CCITT G4, ZLIB (Flate), MRC* 8/24 bit – JPEG, ZLIB (Flate), MRC* TIFF: 1 bit – CCITT G4, LZW, Packbits 8/24 bit – LZW, JPEG, Packbits JPG: 8/24 bit – JPEG *Note: MRC is available only if ISD is installed.	
Supported Scan Destinations	Email, Front-side USB Drive, FTP, LDSS, Network or USB-connected Computer, Windows Network Folder	

DEVICE MANAGEMENT		
System Specification	Xerox® MX831 Multifunction Printer	Xerox® MX833 Multifunction Printer
Device Management	Xerox® Easy Assist App, Remote Operator Panel, Xerox® Embedded Web Server	
Xerox® CentreWare® Web Software	Yes	

ACCESSIBILITY		
System Specification	Xerox® MX831 Multifunction Printer	Xerox® MX833 Multifunction Printer
Accessibility	- Speech talk-back via speaker or headphones - Volume control via gesturing or headphones - USB keyboard support	

SYSTEM SPECIFICATION

Xerox® MX831 and MX833 Multifunction Printers



SINGLE-PASS DUPLEX AUTOMATIC DOCUMENT FEEDER (DADF)

Saves time by simultaneously scanning both sides of two-sided documents at up to 160/152 ipm Letter/A4. A 200-sheet capacity and multifeed detection help streamline large scan jobs while supporting reliable document capture.

7-INCH COLOR TOUCHSCREEN

Intuitive interface with quick access to workflows, apps, and everyday tasks.

Finishing:



STAPLE FINISHER

Single-position stapling for up to 50 sheets, plus a 500-sheet output bin with job offset stacking.



STAPLE HOLE PUNCH FINISHER

Includes all Staple Finisher capabilities, plus automatic 2-, 3-, or 4-hole punching and dual-position stapling, including landscape stapling.



4-BIN MAILBOX

Provides four 100-sheet output bins for job separation and supports up to three mailbox units for a total of 12 bins and 1,200 additional output sheets.



100-SHEET MULTIPURPOSE FEEDER

Includes support for specialty media and custom paper sizes.

550-SHEET TRAY

Includes support for Letter, Legal and Envelopes.

Optional Accessories:



CASTER BASE

Allows floor-standing devices to be moved easily.



500GB HARD DISK

Provides the highest storage capacity for large jobs, document storage, and advanced workflows.



CARD READERS

Enables secure card-based user authentication.

Optional paper feeding:



550-SHEET TRAY

Add up to three additional 550-Sheet trays for extra capacity.



2,100-SHEET TRAY

Add an optional 2,100-Sheet tray to maximize capacity. (Caster Base required.)

SYSTEM SPECIFICATION

Xerox® MX831 and MX833 Multifunction Printers



SECURITY		
System Specification	Xerox® MX831 Multifunction Printer	Xerox® MX833 Multifunction Printer
Security Protocols/Features	Hardware-enabled Post-Quantum Cryptography, Digitally Signed Firmware Updates, Trusted Platform Module (TPM 2.0), WPA3, TLS 1.3, OpenSSL cryptographic module validated to FIPS 140-3, Certificate Management, Secure Password Reset, TCP Connection Filtering, Port Filtering, Access Controls, Confidential Print, Non-Volatile Memory Wipe, Fax/Network Separation, Protected USB Ports, Auto-insertion of Sender's Email Address, Login Restrictions, Audit Log, Syslog	
WI-FI SECURITY		
Authentication and Encryption Methods	802.11a/b/g/n/ac, Infrastructure (BSS) Mode, WEP Encryption (64 and 128-bit keys), WPA2/WPA Personal AES PSK, WPA2-Personal, WPA3-Personal, WPA2/WPA3-Personal, 802.1x: EAP-MD5, EAP-MSCHAPv2, EAP-TLS, EAP-TTLS (CHAP/MSCHAPv2/PAP), LEAP, PEAP	

PAPER HANDLING		
System Specification	Xerox® MX831 Multifunction Printer	Xerox® MX833 Multifunction Printer
SINGLE-PASS DUPLEX AUTOMATIC DOCUMENT FEEDER (DADF)		
Capacity ³	200 sheets of 20 lb bond/75 gsm	
Minimum Media Size	3x5 in	
Minimum Media Size	76.2x127 mm	
Maximum Media Size	8.5x25 in	
Maximum Media Size	216x635 mm	
Minimum to Maximum Media Weights	52–120 gsm	
PLATEN		
Maximum Media Size	8.5x14 in	
Maximum Media Size	216x356 mm	
MULTIPURPOSE FEEDER		
Capacity ³	100 sheets of 20 lb bond/75 gsm	
Minimum Media Size	3x5 in	
Minimum Media Size	76.2x127 mm	
Maximum Media Size	8.5x14 in	
Maximum Media Size	216x356 mm	
Minimum to Maximum Media Weights	60–220 gsm	
Media Types Supported	Light Paper, Plain Paper, Heavy Paper, Cardstock, Envelopes, Labels, Recycled, Glossy, Heavy Glossy, Bond, Rough Envelope, Letterhead, Preprinted, Colored Paper, Rough/Cotton, Custom Type	
MAIN TRAY		
Capacity ³	550 sheets of 20 lb bond/75 gsm	
Minimum Media Size	3x5.83 in	
Minimum Media Size	76.2x148 mm	
Maximum Media Size	8.5x14 in	
Maximum Media Size	216x356 mm	
Minimum to Maximum Media Weights	60-220 gsm	

SYSTEM SPECIFICATION

Xerox® MX831 and MX833 Multifunction Printers



PAPER HANDLING		
System Specification	Xerox® MX831 Multifunction Printer	Xerox® MX833 Multifunction Printer
MAIN TRAY		
Media Types Supported	Light Paper, Plain Paper, Heavy Paper, Cardstock, Envelopes, Labels, Recycled, Glossy, Heavy Glossy, Bond, Rough Envelope, Letterhead, Preprinted, Colored Paper, Rough/Cotton, Custom Type	
OPTIONAL 550-SHEET TRAY		
Capacity ³	550 sheets of 20 lb bond/75 gsm	
Minimum Media Size	3x5.83 in	
Minimum Media Size	76.2x148 mm	
Maximum Media Size	8.5x14 in	
Maximum Media Size	216x356 mm	
Minimum to Maximum Media Weights	60–220 gsm	
Media Types Supported	Light Paper, Plain Paper, Heavy Paper, Cardstock, Envelopes, Labels, Recycled, Glossy, Heavy Glossy, Bond, Rough Envelope, Letterhead, Preprinted, Colored Paper, Rough/Cotton, Custom Type	
OPTIONAL 2,100-SHEET TRAY		
Capacity ³	2100 sheets of 20 lb bond/75 gsm	
Minimum Media Size	8.27x5.83 in	
Minimum Media Size	210x148 mm	
Maximum Media Size	8.5x14 in	
Maximum Media Size	216x356 mm	
Minimum to Maximum Media Weights	60 - 135 gsm	
Media Types Supported	Light Paper, Plain Paper, Heavy Paper, Recycled, Bond, Letterhead, Preprinted, Custom Type	
STANDARD/ MAXIMUM INPUT CAPACITY		
Standard Input Capacity ³	650	
Maximum Input Capacity ³	3,300	
OUTPUT CAPACITY		
Standard Output Capacity ³	550	

SYSTEM SPECIFICATION

Xerox® MX831 and MX833 Multifunction Printers



FINISHING		
System Specification	Xerox® MX831 Multifunction Printer	Xerox® MX833 Multifunction Printer
Staple Finisher with Offset Stacking (Optional)	500-sheet output stacker, 50-sheet stapling, multi-position stapling and offset stacking	
Staple Hole Punch Finisher (Optional)	500-sheet output stacker, 50-sheet multi-position stapling with integrated 2-/3-hole punching	
4-Bin Mailbox (Optional)	Four 100-sheet bins (400 sheets total) for mailbox, copy, print and fax job separation, offset stacking and multi-user output sorting	
DIMENSIONS AND WEIGHTS		
Staple Finisher with Offset Stacking (Unpackaged)	Width: 17.1 in/435 mm Depth: 16.3 in/414 mm Height: 9.7 in/246 mm Weight: 16.0 lb/7.30 kg	
Staple Hole Punch Finisher (Unpackaged)	Width: 18.2 in/462 mm Depth: 20.0 in/507 mm Height: 10.3 in/263 mm Weight: 25.0 lb/11.40 kg	
4-Bin Mailbox (Unpackaged)	Width: 16.6 in/421 mm Depth: 15.1 in/384 mm Height: 10.7 in/271.5 mm Weight: 13.9 lb/6.30 kg	
Staple Finisher with Offset Stacking (Packaged)	Width: 21.42 in/544 mm Depth: 20.71 in/526 mm Height: 16.38 in/416 mm Weight: 19.7 lb/8.94 kg	
Staple Hole Punch Finisher (Packaged)	Width: 23.31 in/592 mm Depth: 16.77 in/426 mm Height: 24.09 in/612 mm Weight: 31.2 lb/14.15 kg	
4-Bin Mailbox (Packaged)	Width: 21.97 in/558 mm Depth: 19.65 in/499 mm Height: 16.85 in/428 mm Weight: 17.8 lb/8.07 kg	

SYSTEM SPECIFICATION

Xerox® MX831 and MX833
Multifunction Printers



DEVICE SPECIFICATION		
System Specification	Xerox® MX831 Multifunction Printer	Xerox® MX833 Multifunction Printer
ELECTRICAL REQUIREMENTS		
North America and other low-volt regions	Voltage: 110–127 VAC +/-10%; Current: 10 A. Frequency: 50–60 Hz	
Europe and other high-volt regions	Voltage: 220–240 VAC +/-10%; Current: 5 A. Frequency: 50–60 Hz	
POWER CONSUMPTION		
Printing (Average)	Simplex: 714 W; Duplex: 529 W	Simplex: 896 W; Duplex: 656 W
Typical Electricity Consumption (kWh)	0.69	0.96
Ready Mode	31.8 W	30.6 W
Sleep Mode	0.92 W	0.95 W
OPERATING ENVIRONMENT AND ACOUSTICS		
Required Temperature Range	50 to 90°F/10 to 32.2°C	
Required Relative Humidity (RH)	15 to 80% RH	
Sound Power Levels Operating	7.0 Bels(A) or less	7.2 Bels(A) or less
Standby	3.2 Bels(A) or less	
Sound Pressure Levels Operating	53 dB(A)	55 dB(A)
Standby	14 dB(A)	

SYSTEM SPECIFICATION

Xerox® MX831 and MX833 Multifunction Printers



DIMENSIONS AND WEIGHTS		
System Specification	Xerox® MX831 Multifunction Printer	Xerox® MX833 Multifunction Printer
MX831/MX833 (Devices Unpackaged)	Width: 21.9 in / 556.9 mm Depth: 22.0 in / 559 mm Height: 35.8 in / 908.1 mm Weight: 96.5 lb / 43.8 kg	Width: 21.9 in / 556.9 mm Depth: 22.0 in / 559 mm Height: 35.8 in / 908.1 mm Weight: 96.5 lb / 43.8 kg
550-Sheet Tray (Unpackaged)	Width: 20.1 in / 510 mm Depth: 22.0 in / 559 mm Height: 4.3 in / 110 mm Weight: 12.8 lb / 5.82 kg	
2,100-Sheet Tray (Unpackaged)	Width: 20.1 in / 510 mm Depth: 22.0 in / 559 mm Height: 13.8 in / 350 mm Weight: 39 lb / 17.73 kg	
Caster Base (Unpackaged)	Width: 23.7 in / 601.98 mm Depth: 27 in / 685.8 mm Height: 4.2 in / 106.7 mm Weight: 20.2 lb / 9.2 kg	
550-Sheet Tray (Packaged)	Width: 23.5 in / 598.0 mm Depth: 24.8 in / 630.0 mm Height: 7.7 in / 196 mm Weight: 21.2 lb / 9.6 kg	
2100-Sheet Tray (Packaged)	Width: 25.24 in / 641 mm Depth: 27.17 in / 690 mm Height: 18.62 in / 473 mm Weight: 53.4 lb / 24.22 kg	
Caster Base (Packaged)	Width: 31.54 in / 801 mm Depth: 31.22 in / 793 mm Height: 10.27 in / 261 mm Weight: 33.42 lb / 15.16 kg	

SYSTEM SPECIFICATION
Xerox® MX831 and MX833
Multifunction Printers



INSTALLATION CONSIDERATIONS		
System Specification	Xerox® MX831 Multifunction Printer	Xerox® MX833 Multifunction Printer
Ventilation clearance requirements. The table below shows the area needed on each side for correct installation.		
Top	6 in/152 mm	
Rear	6 in/152 mm	
Left	6 in/152 mm	
Right	6 in/152 mm	
Front	16 in/406 mm	

SYSTEM CERTIFICATION / REGULATORY COMPLIANCE		
System Specification	Xerox® MX831 Multifunction Printer	Xerox® MX833 Multifunction Printer
Certifications	To view the latest list of certifications, visit xerox.com .	

WHAT'S IN THE BOX		
System Specification	Xerox® MX831 Multifunction Printer	Xerox® MX833 Multifunction Printer
All items contained in the box	• Xerox® MX831 Multifunction Printer • Power Cord • Installation Guide • Product Safety Sheet • Black Cartridge: 7,500 Print Capacity⁴	• Xerox® MX833 Multifunction Printer • Power Cord • Installation Guide • Product Safety Sheet • Black Cartridge: 7,500 Print Capacity⁴

SYSTEM SPECIFICATION

Xerox® MX831 and MX833
Multifunction Printers



SUPPLIES AND ACCESSORIES

System Specification	Part Number
Genuine Xerox Black Standard Capacity Toner Cartridge, 15,000 Pages ⁴	Supplies part numbers are available at xerox.com/regional-supplies
Genuine Xerox Black High Capacity Toner Cartridge, 35,000 Pages ⁴	
Genuine Xerox Black Extra High Capacity Toner Cartridge, 73,800 Pages ^{4**}	
Imaging Unit, 225,000 Pages	

OPTIONAL ACCESSORIES

System Specification	Part Number
550-Sheet Tray	097S05329
2100-Sheet Tray	097S05328
Caster Base	497K26960
4-Bin Mailbox	097S05334
Staple Finisher with Offset Stacking	097S05335
Staple Hole Punch Finisher	097S05336
English Keyboard	497K26270
Card Reader (USB Contactless Front Reader TWN4 MultiTech-P LEGIC)	497K26210
Card Reader (USB Contactless Front Reader TWN MultiTech-PI)	497K25970
500GB Hard Disk	497K26250
256GB SSD	497K27370
Removable HDD Enclosure Kit	497K26260
2 Port Fax Card	497K26240

SYSTEM SPECIFICATION

Xerox® MX831 and MX833
Multifunction Printers



¹ Declared print speed in accordance with ISO/IEC 24734.

² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

³ Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.

⁴ Average standard pages. Declared yield in accordance with ISO/IEC 19752. Yield will vary based on image, area coverage and job run length.

For more information,
visit us at www.xerox.com/en-us/office



© 2026 Xerox Corporation. All rights reserved. Xerox®, CentreWare®, the Xerox logo and spark graphic are trademarks of XRX Brandco LLC in the United States and/or other countries. The information in this brochure is subject to change without notice. 10/26 REF-1503604 BR43201 MX8SS-01UA